

# KBT600MB

**Product family** Hood

**Hood Type** Decorative wall hood

Design T flat Extraction Extraction Yes **Electronic control** 

Material Stainless steel 8017709347239 **EAN** code

Hood width 60 cm **Aesthetic** Universale Colour Matt Black Silk screen Logo



#### **Controls**

Control setting Electronic buttons

## **Program / Functions**

No. of speeds Intensive speed

24h air filter function

Time-setting options







### **Technical Features**









No. of lights 2 Light type LED **Light Power** 1.3 W 3000 K Light color temperature

scale (K)

Free outlet maximum 820 m<sup>3</sup>/h

capacity

230 W Motor power No. of filters 2

Anti-grease filters Filter replacement

indicator

Vent outlet Minimum distance from

**GAS** hob

Minimum distance from **ELECTRIC hob** 

Aluminium

Yes

150 mm 650 mm

500 mm

Non return valve Yes

**SMEG SPA** 30/11/2025



	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	260	49
Speed 2	358	57
Speed 3	473	64
Intensive speed	686	72

### Accessories included

Tube reduction Yes

## Performance / Energy Label

<	A'

Airbourne acouistical A- 48 dBA **Annual Efficiency** 53 kWh/a Consumption (AEChood) weighted sound Power Emission at minimum Energy efficieency class A speed (SPEmin) (EEC) Airborne acoustical A-64 dBA Fluid Dynamic Efficiency 29.8 weighted sound Power (FDE) **Emission at maximum** Fluid Dynamic Efficiency A speed (SPEmax) class (FDEC) Airbourne acoustical A- 71 dBA Lighting Efficiency (LE) 70.4 lux/W weighted sound power Lighting Efficiency Class A emission at boost speed (LEC) (SPEboost) **Grease Filtering** 79.7 % Time increase factor (F) Efficiency (GFE) **Energy Efficiency Index Grease Filtering** C Measured air flow rate 395 m<sup>3</sup>/h Efficiency Class (GFEC) at best efficiency point Air flow at minumum 261 m<sup>3</sup>/h (Qbep) speed (Qmin) Measured air pressure 451 Pa Air flow at maximum 473 m<sup>3</sup>/h at best efficiency point speed (Qmax) (Pbep) Air flow at boost speed 686 m<sup>3</sup>/h Measured electric 159 W (Qboost) power input at best efficiency point (Wbep) **Nominal Power** 3 W consumption of the light system (WL) Average illumination of 156 lux

#### **Electrical Connection**

SMEG SPA 30/11/2025

the light on the cooking surface (Emiddle) Sound power level at

highest setting (Lwa)

70 dBA



Electrical connection rating

230 W

Voltage

Frequency (Hz)

220-240 V 50-60 Hz Power supply cable length

Plug

1500 mm

Not present

SMEG SPA 30/11/2025



# **Compatible Accessories**



#### **KITCEKBTMB**



#### **KITFCKBT**

1 pc of charcoal filter for the hood models KBT\* / KBCT\*





1 pcs of Charcoal filter Regenerable\* suitable for all the KBT/KBCT models. \* It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm

SMEG SPA 30/11/2025



## Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Energy efficiency class A



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.

SMEG SPA 30/11/2025