

# KBT600MB

## Product family

Hood

## Hood Type

Decorative wall hood

## Design

T flat

## Extraction

Extraction

## Electronic control

Yes

## Material

Stainless steel

## EAN code

8017709347239

## Hood width

60 cm

## Aesthetic

Universale

## Colour

Matt Black

## Logo

Silk screen



## Controls

### Control setting

Electronic buttons

## Program / Functions

### No. of speeds

3

### Intensive speed




### 24h air filter function



### Time-setting options



## Technical Features



### No. of lights

2

### Anti-grease filters

Aluminium

### Light type

LED

### Filter replacement indicator

Yes

### Light Power

1,3 W

### Vent outlet

150 mm

### Light color temperature scale (K)

3000 K

### Minimum distance from GAS hob

650 mm

### Free outlet maximum capacity

820 m<sup>3</sup>/h

### Minimum distance from ELECTRIC hob

500 mm

### Motor power

230 W

### Non return valve

Yes

### No. of filters

2

	Extraction rate IEC 61591 [m <sup>3</sup> /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	260	49
Speed 2	358	57
Speed 3	473	64
Intensive speed	686	72

## Accessories included

Tube reduction Yes

## Performance / Energy Label



**Annual Efficiency Consumption (AEChood)** 53 kWh/a  
**Energy efficicency class (EEC)** A  
**Fluid Dynamic Efficiency (FDE)** 29,8  
**Fluid Dynamic Efficiency class (FDEC)** A  
**Lighting Efficiency (LE)** 70,4 lux/W  
**Lighting Efficiency Class (LEC)** A  
**Grease Filtering Efficiency (GFE)** 79,7 %  
**Grease Filtering Efficiency Class (GFEC)** C  
**Air flow at minumum speed (Qmin)** 261 m<sup>3</sup>/h  
**Air flow at maximum speed (Qmax)** 473 m<sup>3</sup>/h  
**Air flow at boost speed (Qboost)** 686 m<sup>3</sup>/h

**Airbourne acoustical A- weighted sound Power Emission at minimum speed (SPEmin)** 48 dBA  
**Airborne acoustical A- weighted sound Power Emission at maximum speed (SPEmax)** 64 dBA  
**Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost)** 71 dBA  
**Time increase factor (F)** 0,9  
**Energy Efficiency Index** 52,0  
**Measured air flow rate at best efficiency point (Qbep)** 395 m<sup>3</sup>/h  
**Measured air pressure at best efficiency point (Pbep)** 451 Pa  
**Measured electric power input at best efficiency point (Wbep)** 159 W  
**Nominal Power consumption of the light system (WL)** 3 W  
**Average illumination of the light on the cooking surface (Emiddle)** 156 lux  
**Sound power level at highest setting (Lwa)** 70 dBA

## Electrical Connection




---

<b>Electrical connection rating</b>	230 W	<b>Power supply cable length</b>	1500 mm
<b>Voltage</b>	220-240 V	<b>Plug</b>	Not present
<b>Frequency (Hz)</b>	50-60 Hz		

## Compatible Accessories




**KITCEKBTMB**



**KITFCKBT**

1 pc of charcoal filter for the hood models KBT\* / KBCT\*



**KITFCKBTR**

1 pcs of Charcoal filter Regenerable\* suitable for all the KBT/KBCT models. \* It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm

## Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Energy efficiency class A



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.