

KBT600VE

Product family	Hood
Hood Type	Chimney Cooker Hoods
Design	T flat
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Material	Stainless Steel + Glass
Type of steel	Brushed
EAN code	8017709289713
Hood width	60 cm
Aesthetics	Universal
Colour	Stainless Steel and Glass
Finishing	Brushed
Logo	Silk screen



Controls

Control setting	Electronic buttons
------------------------	--------------------

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	

Technical Features



No. of lights	2	Anti-grease filters	Aluminium
Light type	LED	Filter replacement indicator	Yes
Light power	1.3 W	Vent outlet	150 mm
Light colour	3000 K	Minimum distance from GAS hob	650 mm
temperature scale (K)		Minimum distance from ELECTRIC hob	500 mm
Free outlet maximum capacity	730 m³/h	Non return valve	Yes
Motor power	230 W		
No. of filters	1		

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	243	48
Speed 2	332	55
Speed 3	451	62
Intensive speed	677	71

Accessories Included

Tube reduction Yes

Performance / Energy Label

	Annual Efficiency Consumption (AEChood)	60 kWh/year	Airbourne acoustical weighted sound Power Emission at minimum speed (SPEmin)	47 dBA
	Energy efficiency class (EEC)		Airborne acoustical weighted sound Power Emission at maximum speed (SPEmax)	61 dBA
	Fluid Dynamic Efficiency (FDE)	29.1	Airbourne acoustical weighted sound power emission at boost speed (SPEboost)	70 dBA
	Fluid Dynamic Efficiency class (FDEC)	A	Time increase factor (F)	1.0
	Lighting Efficiency (LE)	68.5 lux/W	Energy Efficiency Index per first cavity	57.4
	Lighting Efficiency Class (LEC)	A	Measured air flow rate at best efficiency point (Qbep)	433 m ³ /h
	Grease Filtering Efficiency (GFE)	81.1 %	Measured air pressure at best efficiency point (Qbep)	451 Pa
	Grease Filtering Efficiency Class (GFEC)	C	Measured electric power input at best efficiency point (Wbep)	158 W
	Air flow at minimum speed (Qmin)	243 m ³ /h	Normal Power of the light system (WI)	3 W
	Maximum extraction rate	451 m ³ /h	Average illumination of the light on the cooking surface (Emiddle)	178 lux
	Intensive extraction rate	677 m ³ /h	Sound power level at highest setting (Lwa)	62 dBA

Electrical Connection

Nominal power 233 W

Voltage
Frequency (Hz)


220-240 V
50-60 Hz

Power supply cable length

1500 mm

Plug


No




Compatible Accessories

**KITCEKBT**

Chimney extension, dimensions 261,5 * 260 * 830 mm suitable for T-shape hood KBT* & KBCT*, max hight 1380 mm Stainless Steel

**KITFCKBT**

1 pcs of activated carbon filter for hood models KBT* / KBCT*

**KITFCKBTR**

1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm

Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.