KBT600VE

Product family	Hood
Hood Type	Chimney Cooker Hoods
Design	T flat
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Material	Stainless Steel + Glass
Type of steel	Brushed
EAN code	8017709289713
Hood width	60 cm
Aesthetics	Universal
Colour	Stainless Steel and Glass
Finishing	Brushed
Logo	Silk screen



Controls

Control setting	Electronic buttons

Program / Functions

No. of speeds	3
Intensive speed	BOOST
24h air filter function	24
Time-setting options	

Technical Features

No. of lights	2	**Anti-grease filters**	Aluminium
Light type	LED	**Filter replacement indicator**	Yes
Light power	1,3 W	**Vent outlet**	150 mm
Light colour temperature scale (K)	3000 K	**Minimum distance from GAS hob**	650 mm
Free outlet maximum capacity	730 m³/h	**Minimum distance from ELECTRIC hob**	500 mm
Motor power	230 W	**Non return valve**	Yes
No. of filters	1		

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	243	48
Speed 2	332	55
Speed 3	451	62
Intensive speed	677	71

Accessories Included

Tube reduction	Yes

Performance / Energy Label




Annual Efficiency Consumption (AEChood)	60 kWh/year
Energy efficiency class (EEC)	B
Fluid Dynamic Efficiency (FDE)	29,1
Fluid Dynamic Efficiency class (FDEC)	A
Lighting Efficiency (LE)	68,5 lux/W
Lighting Efficiency Class (LEC)	A
Grease Filtering Efficiency (GFE)	81,1 %
Grease Filtering Efficiency Class (GFEC)	C
Air flow at minumum speed (Qmin)	243 m³/h
Maximum extraction rate	451 m³/h
Intensive extraction rate	677 m³/h

Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin)	47 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)	61 dBA
Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)	70 dBA
Time increase factor (F)	1,0
Energy Efficiency Index per first cavity	57,4
Measured air flow rate at best efficiency point (Qbep)	433 m³/h
Measured air pressure at best efficiency point (Qbep)	451 Pa
Measured electric power input at best efficiency point (Wbep)	158 W
Normal Power of the light system (Wl)	3 W
Average illumination of the light on the cooking surface (Emiddle)	178 lux
Sound power level at highest setting (Lwa)	62 dBA

Electrical Connection

Nominal power	233 W

Voltage	220-240 V	**Power supply cable length**	1500 mm
Frequency (Hz)	50-60 Hz		
		Plug	No




Compatible Accessories




KITCEKBT

Chimney extension, dimensions 261,5 * 260 * 830 mm suitable for T-shape hood KBT* & KBCT*, max hight 1380 mm Stainless Steel



KITFCKBTR

1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm



KITFCKBT

1 pcs of activated carbon filter for hood models KBT* / KBCT*

Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Warning light(s): to advise when filters need changing.



Intensive/turbo setting: when extra fast extraction is required.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.





Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.