

KBT600VE

Product family	Hood
Hood Type	Decorative wall hood
Design	T flat
Extraction	Extraction
Electronic control	Yes
Material	Stainless Steel + Glass
Type of steel	Brushed
EAN code	8017709289713
Hood width	60 cm
Aesthetic	Universale
Colour	Stainless Steel and Glass
Finishing	Satin
Logo	Silk screen




Controls

Control setting	Electronic buttons
------------------------	--------------------

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	

Technical Features



No. of lights	2	Anti-grease filters	Aluminium
Light type	LED	Filter replacement indicator	Yes
Light Power	1,3 W	Vent outlet	150 mm
Light color temperature scale (K)	3000 K	Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	730 m ³ /h	Minimum distance from ELECTRIC hob	500 mm
Motor power	230 W	Non return valve	Yes
No. of filters	1		

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	243	48
Speed 2	332	55
Speed 3	451	62
Intensive speed	677	71

Accessories included

Tube reduction Yes

Performance / Energy Label




Annual Efficiency Consumption (AEChood) 60 kWh/a
Energy efficicency class (EEC) B
Fluid Dynamic Efficiency (FDE) 29,1
Fluid Dynamic Efficiency class (FDEC) A
Lighting Efficiency (LE) 68,5 lux/W
Lighting Efficiency Class (LEC) A
Grease Filtering Efficiency (GFE) 81,1 %
Grease Filtering Efficiency Class (GFEC) C
Air flow at minumum speed (Qmin) 243 m³/h
Air flow at maximum speed (Qmax) 451 m³/h
Air flow at boost speed (Qboost) 677 m³/h

Airbourne acoustical A- weighted sound Power Emission at minimum speed (SPEmin) 47 dBA
Airborne acoustical A- weighted sound Power Emission at maximum speed (SPEmax) 61 dBA
Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost) 70 dBA
Time increase factor (F) 1,0
Energy Efficiency Index 57,4
Measured air flow rate at best efficiency point (Qbep) 433 m³/h
Measured air pressure at best efficiency point (Pbep) 451 Pa
Measured electric power input at best efficiency point (Wbep) 158 W
Nominal Power consumption of the light system (WL) 3 W
Average illumination of the light on the cooking surface (Emiddle) 178 lux
Sound power level at highest setting (Lwa) 62 dBA

Electrical Connection


Electrical connection rating	233 W	Power supply cable length	1500 mm
Voltage	220-240 V	Plug	Not present
Frequency (Hz)	50-60 Hz		




Compatible Accessories

**KITCEKBT**

Chimney extension, dimensions 261,5 * 260 * 830 mm suitable for T-shape hood KBT* & KBCT*, max height 1380 mm Stainless Steel

**KITFCKBT**

1 pc of charcoal filter for the hood models KBT* / KBCT*

**KITFCKBTR**

1 pc of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm

Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.