

KBT600XE

Product family Hood

Hood Type Chimney Cooker Hoods

Design

Extraction Ducted out or re-circulation possible

Electronic control Yes

Material Stainless steel Type of steel Brushed

EAN code 8017709286613

Hood width 60 cm



Aesthetics

Universal Brushed **Aesthetics Finishing** Colour Stainless steel Logo Silk screen

Controls

Electronic buttons Control setting

Programs / Functions

No. of speeds Intensive speed

24h air filter function

Time-setting options







Technical Features









No. of lights 2 Light type LED Light power 1.3 W 3000 °K Light colour

temperature scale (°K)

Anti-grease filters

Filter replacement

indicator

Vent outlet Minimum distance from

GAS hob

Aluminium Yes

150 mm 650 mm

SMEG SPA 03/12/2024



Free outlet maximum

820 m³/h

Minimum distance from

ELECTRIC hob

Motor power

capacity

230 W

Non return valve

Yes

500 mm

No. of filters 2

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	260	49
Speed 2	358	57
Speed 3	473	64
Intensive speed	686	72

Accessories Included

Tube reduction Yes

Performance / Energy Label

A T

Annual Efficiency

53 KWh/year Consumption (AEChood)

Energy efficiency class (A

EEC)

Fluid Dynamic Efficiency 29.8

(FDE)

Fluid Dynamic Efficiency A

class (FDEC)

Lighting Efficiency (LE) 70.4 lux/W

Lighting Efficiency Class A

(LEC)

Grease Filtering 79.7 %

Efficiency (GFE)

Grease Filtering C

Efficiency Class (GFEC)

Air flow at minumum 261 m³/h

speed (Qmin)

Maximum extraction 473 m³/h

rate

Intensive extraction rate 686 m³/h

Airbourne acouistical A- 48 dBA

weighted sound Power **Emission at minimum**

speed (SPEmin)

efficiency point (Wbep)

light system (WI)

power input at best

Average illumination of

Sound power level at highest setting (Lwa)

64 dBA

weighted sound Power **Emission at maximum** speed (SPEmax)

Airborne acoustical A-

Airbourne acoustical A- 71 dBA

weighted sound power emission at boost speed

(SPEboost)

Power Consumption in 0.49 W

Off mode (Po)

Power consumption in 0.23 W

stand-by mode (Ps)

Time increase factor (F) **Energy Efficiency Index** 52.0

per first cavity

Measured air flow rate 395 m³/h

at best efficiency point (Qbep)

Measured air pressure

at best efficiency point (Qbep) Measured electric

159 W

Normal Power of the

156 lux

3 W

451 Pa

the light on the cooking surface (Emiddle)

70 dBA


SMEG SPA 03/12/2024



Electrical Connection

Nominal power 230 W Voltage 220-240 V Frequency (Hz)
Power supply cable
length

50-60 Hz 1500 mm



SMEG SPA 03/12/2024



Not included accessories



KITFCKBT

1 pcs of activated carbon filter for hood models KBT* / KBCT*



KITFCKBTR

1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models.
* It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm



Chimney extension, dimensions 261,5 * 260 * 830 mm suitable for T-shape hood KBT* & KBCT*, max hight 1380 mm Stainless Steel

SMEG SPA 03/12/2024



Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



A: Product drying performance, measured from A+++ to D / G depending on the product family



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.

SMEG SPA 03/12/2024