

KBT900AE

Product family Hood

Hood Type Decorative wall hood

Design T flat Extraction Extraction Yes **Electronic control**

Painted material Material

Type of steel Brushed

EAN code 8017709312961

Hood width 90 cm **Aesthetic** Universale Colour **Anthracite** Logo Silk screen



Controls

Control setting Electronic buttons

Program / Functions

No. of speeds Intensive speed

24h air filter function

Time-setting options







Technical Features









No. of lights 2 Light type LED **Light Power** 1,3 W Free outlet maximum 730 m³/h

capacity

Motor power 230 W No. of filters 3

Anti-grease filters

Aluminium Filter replacement Yes

indicator Vent outlet

Minimum distance from

GAS hob

Minimum distance from

ELECTRIC hob

500 mm

150 mm

650 mm

Non return valve Yes

Extraction rate IEC 61591 [m3/h]

Noise level IEC 60704-2-13 [dBA]



Speed 1	265	47
Speed 2	360	55
Speed 3	480	62
Intensive speed	713	72

Accessories included

Tube reduction Yes

Performance / Energy Label

A f

Annual Efficiency 54 kWh/a Consumption (AEChood) Energy efficieency class A (EEC) Fluid Dynamic Efficiency 31,2 (FDE) Fluid Dynamic Efficiency A class (FDEC) Lighting Efficiency (LE) 60,0 lux/W Lighting Efficiency Class A (LEC) **Grease Filtering** 76,5 % Efficiency (GFE) Grease Filterina Efficiency Class (GFEC) Air flow at minumum 265 m³/h speed (Qmin)

Airbourne acouistical A- 46 dBA weighted sound Power **Emission at minimum** speed (SPEmin) Airborne acoustical A-62 dBA weighted sound Power **Emission at maximum** speed (SPEmax) Airbourne acoustical A- 71 dBA weighted sound power emission at boost speed (SPEboost) Time increase factor (F) 0,9 **Energy Efficiency Index** 52.0 Measured air flow rate 395 m³/h at best efficiency point (Qbep) Measured air pressure 451 Pa at best efficiency point (Pbep) 159 W Measured electric power input at best efficiency point (Wbep)

Nominal Power 3 W consumption of the light system (WL)

Average illumination of the light on the cooking surface (Emiddle)

Sound power level at highest setting (Lwa)

156 lux

62 dBA

Electrical Connection

Electrical connection

Air flow at maximum

Air flow at boost speed

speed (Qmax)

(Qboost)

230 W

480 m³/h

713 m³/h

Power supply cable

1500 mm

rating

Voltage 220-240 V Frequency (Hz) 50-60 Hz length Plug

Not present





Compatible Accessories



KITCEKBTMB



KITFCKBT

1 pc of charcoal filter for the hood models KBT* / KBCT*

KITFCKBTR



1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm



Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Energy efficiency class A



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.