

KBT900BL

| | |
|--------------------|----------------------|
| Product family | Hood |
| Hood Type | Decorative wall hood |
| Design | T flat |
| Extraction | Extraction |
| Electronic control | Yes |
| Material | Stainless steel |
| EAN code | 8017709358815 |
| Hood width | 90 cm |
| Aesthetic | Universale |
| Colour | Black |
| Logo | Silk screen |



Controls

| | |
|-----------------|--------------------|
| Control setting | Electronic buttons |
|-----------------|--------------------|

Program / Functions

| | |
|-------------------------|---|
| No. of speeds | 3 |
| Intensive speed | |
| 24h air filter function | |
| Time-setting options | |

Technical Features



| | | | |
|-----------------------------------|-----------------------|------------------------------------|-----------|
| No. of lights | 2 | Anti-grease filters | Aluminium |
| Light type | LED | Filter replacement indicator | Yes |
| Light Power | 1,3 W | Vent outlet | 150 mm |
| Light color temperature scale (K) | 3000 K | Minimum distance from GAS hob | 650 mm |
| Free outlet maximum capacity | 820 m ³ /h | Minimum distance from ELECTRIC hob | 500 mm |
| Motor power | 230 W | Non return valve | Yes |
| No. of filters | 3 | | |

| | Extraction rate IEC 61591 [m³/h] | Noise level IEC 60704-2-13 [dBA] |
|-----------------|----------------------------------|----------------------------------|
| Speed 1 | 260 | 49 |
| Speed 2 | 360 | 57 |
| Speed 3 | 480 | 62 |
| Intensive speed | 713 | 72 |

Accessories included

Tube reduction Yes

Performance / Energy Label



Annual Efficiency Consumption (AEChood) 53 kWh/a
Energy efficicency class (EEC) A
Fluid Dynamic Efficiency (FDE) 29,8
Fluid Dynamic Efficiency class (FDEC) A
Lighting Efficiency (LE) 70,4 lux/W
Lighting Efficiency Class (LEC) A
Grease Filtering Efficiency (GFE) 79,7 %
Grease Filtering Efficiency Class (GFEC) C
Air flow at minumum speed (Qmin) 261 m³/h
Air flow at maximum speed (Qmax) 473 m³/h
Air flow at boost speed (Qboost) 686 m³/h

Airbourne acoustical A- weighted sound Power Emission at minimum speed (SPEmin) 48 dBA
Airborne acoustical A- weighted sound Power Emission at maximum speed (SPEmax) 64 dBA
Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost) 71 dBA
Time increase factor (F) 0,9
Energy Efficiency Index 52,0
Measured air flow rate at best efficiency point (Qbep) 395 m³/h
Measured air pressure at best efficiency point (Pbep) 451 Pa
Measured electric power input at best efficiency point (Wbep) 159 W
Nominal Power consumption of the light system (WL) 3 W
Average illumination of the light on the cooking surface (Emiddle) 156 lux
Sound power level at highest setting (Lwa) 71 dBA

Electrical Connection

Voltage 220-240 V

Frequency (Hz)


50-60 Hz

Power supply cable
length

1500 mm


Plug

Not present



Compatible Accessories

KITCEKBTBL



KITFCKBT

1 pc of charcoal filter for the hood models KBT* / KBCT*

KITFCKBTR



1 pcs of Charcoal filter Regenerable*
suitable for all the KBT/KBCT models. * It
can be washed in the dishwasher up to
12 times and dry in the oven at max 90°
for 60 min. dimension 237,5(H)x245x10
mm

Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Energy efficiency class A



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.