

KBT900NE




Product family	Hood
Hood Type	Decorative wall hood
Design	T flat
Extraction	Extraction
Electronic control	Yes
Material	Painted material
Type of steel	Brushed
EAN code	8017709299811
Aesthetic	Universale
Colour	Matt Black
Finishing	Matt
Logo	Silk screen



Controls

Control setting	Electronic buttons
-----------------	--------------------

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	

Technical Features



No. of lights	2	Anti-grease filters	Aluminium
Light type	LED	Filter replacement indicator	Yes
Light Power	1.3 W	Vent outlet	150 mm
Free outlet maximum capacity	730 m³/h	Minimum distance from GAS hob	650 mm
Motor power	230 W	Minimum distance from ELECTRIC hob	500 mm
No. of filters	3	Non return valve	Yes

Extraction rate IEC
61591 [m³/h]

Noise level IEC 60704-
2-13 [dBA]

Speed 1	265	47
Speed 2	360	55
Speed 3	480	62
Intensive speed	713	72

Accessories included

Tube reduction Yes

Performance / Energy Label




Annual Efficiency Consumption (AEChood) 54 kWh/a
Energy efficiency class (EEC) A
Fluid Dynamic Efficiency (FDE) 31,2
Fluid Dynamic Efficiency class (FDEC) A
Lighting Efficiency (LE) 60,0 lux/W
Lighting Efficiency Class (LEC) A
Grease Filtering Efficiency (GFE) 76,5 %
Grease Filtering Efficiency Class (GFEC) C
Air flow at minumum speed (Qmin) 265 m³/h
Air flow at maximum speed (Qmax) 480 m³/h
Air flow at boost speed (Qboost) 713 m³/h

Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) 46 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) 62 dBA
Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost) 71 dBA
Time increase factor (F) 0,9
Energy Efficiency Index 52,0
Measured air flow rate at best efficiency point (Qbep) 395 m³/h
Measured air pressure at best efficiency point (Pbep) 451 Pa
Measured electric power input at best efficiency point (Wbep) 159 W
Nominal Power consumption of the light system (WL) 3 W
Average illumination of the light on the cooking surface (Emiddle) 156 lux
Sound power level at highest setting (Lwa) 62 dBA

Electrical Connection

Plug Not present
Electrical connection rating 230 W
Voltage 220-240 V


Frequency (Hz) 50-60 Hz
Power supply cable length 1500 mm



Compatible Accessories




KITCEKBTMB



KITFCKBT

1 pcs di filtro a carboni attivi per i modelli di cappe KBT* / KBCT*



KITFCKBTR

1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm

Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Warning light(s): to advise when filters need changing.



Intensive/turbo setting: when extra fast extraction is required.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.