

KBT900VE




Product family	Hood
Hood Type	Chimney Cooker Hoods
Design	T flat
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Material	Stainless Steel + Glass
Type of steel	Brushed
EAN code	8017709289706
Aesthetics	Universal
Colour	Stainless steel
Finishing	Brushed
Logo	Silk screen



Controls

Control setting	Electronic buttons
-----------------	--------------------

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	

Technical Features

				
No. of lights	2		Anti-grease filters	Aluminium
Light type	LED		Filter replacement indicator	Yes
Light power	1.3 W		Vent outlet	150 mm
Light colour	3000 °K		Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	730 m³/h		Minimum distance from ELECTRIC hob	500 mm
Motor power	230 W		Non return valve	Yes
No. of filters	1			

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	243	48
Speed 2	332	55
Speed 3	451	62
Intensive speed	677	71

Accessories Included

Tube reduction Yes

Performance / Energy Label



Annual Efficiency Consumption (AEChood) 60 KWh/year

Energy efficiency class (EEC) B

Fluid Dynamic Efficiency (FDE) 29,1

Fluid Dynamic Efficiency class (FDEC) A

Lighting Efficiency (LE) 71,0 lux/W

Lighting Efficiency Class (LEC) A

Grease Filtering Efficiency (GFE) 81,1 %

Grease Filtering Efficiency Class (GFEC) C

Air flow at minumum speed (Qmin) 243 m³/h

Maximum extraction rate 451 m³/h

Intensive extraction rate 677 m³/h

Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) 47 dBA

Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) 62 dBA

Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost) 70 dBA

Time increase factor (F) 1,0

Energy Efficiency Index per first cavity 59,5

Measured air flow rate at best efficiency point (Qbep) 383 m³/h

Measured air pressure at best efficiency point (Qbep) 433 Pa

Measured electric power input at best efficiency point (Wbep) 158 W

Normal Power of the light system (WI) 3 W

Average illumination of the light on the cooking surface (Emiddle) 186 lux

Sound power level at highest setting (Lwa) 62 dBA

Electrical Connection

Nominal power 233 W


Frequency (Hz) 50-60 Hz

Voltage

220-240 V

Power supply cable
length

1500 mm



Compatible Accessories



KITCEKBT

Chimney extension, dimensions 261,5 * 260 * 830 mm suitable for T-shape hood KBT* & KBCT*, max height 1380 mm Stainless Steel



KITFCKBT

1 pcs of activated carbon filter for hood models KBT* / KBCT*



KITFCKBTR

1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm

Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.