

KC16A0E

Product family Hood

Hood Type Decorative wall hood

Design Chimney
Extraction Extraction
Material Heat-moulded
EAN code 8017709211721

Hood width 60 cm

Aesthetic Cortina

Colour Anthracite

Components finishing Antique brass

Logo Applied



Controls

Control settingControl knobsControl knobsCortinaNo. of controls2Controls colourAnthracite

Program / Functions

No. of speeds Intensive speed

Technical Features



No. of lights2Motor power275 WLight typeLEDNo. of filters2

Light Power 1 W Anti-grease filters Aluminium
Light color temperature 3000 K Vent outlet 150 mm
scale (K) Non return valve Yes

Free outlet maximum 820 m³/h

capacity

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	337	50
Speed 2	439	57
Speed 3	582	64



ISDEEU	Intensive speed	798	71
--------	-----------------	-----	----

Performance / Energy Label

A T

Annual Efficiency 56 kWh/a Consumption (AEChood) Energy efficieency class A (EEC) Fluid Dynamic Efficiency 25,9 (FDE) Fluid Dynamic Efficiency A class (FDEC) Lighting Efficiency (LE) 128,6 lux/W Lighting Efficiency Class A (LEC) **Grease Filtering** 78 % Efficiency (GFE) **Grease Filtering** C Efficiency Class (GFEC) Air flow at minumum 337 m³/h

speed (Qmin)
Air flow at maximum 582 m³/h
speed (Qmax)
Air flow at boost speed 798 m³/h
(Qboost)

Airbourne acouistical A- 50 dBA weighted sound Power Emission at minimum speed (SPEmin)

Airborne acoustical A- 64 dBA weighted sound Power Emission at maximum speed (SPEmax)

Airbourne acoustical A- 71 dBA

Airbourne acoustical A- 71 dBA weighted sound power emission at boost speed (SPEboost)

Time increase factor (F) 1,00 Energy Efficiency Index 52 Measured air flow rate 412 m³/h

at best efficiency point (Qbep)

Measured air pressure at best efficiency point

(Pbep)

Measured electric 166 W
power input at best
efficiency point (Wbep)
Nominal Power 2 W

consumption of the light system (WL)

Average illumination of the light on the cooking

surface (Emiddle)

Sound power level at highest setting (Lwa)

Electrical Connection

Electrical connection

rating

Voltage 220-240 V Frequency (Hz) 50-60 Hz Power supply cable

length

Plug

1000 mm

451 Pa

283 lux

64 dBA

Not present

Also available

Alternative colours available

Cream

277 W

Available colours

KC16A0E

Optional accessories



Charcoal filter

FLT6

Kit with aesthetic components

KITKCS-2/ KITKCX-2/ KITLOGOCR/ KITLOGOAS



Compatible Accessories

FLT6

Round Charcoal filters (kit 2 pieces)







KIT LOGO & HANDRAIL BRASS FINISHING



SMEG

KIT LOGO ANTIQUE SILVER FINISHING



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

KITKCX-2



KIT LOGO & HANDRAIL CHROME FINISHING

KITLOGOCR



KIT LOGO CHROME FINISHING



Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Energy efficiency class A



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.