

KC19A0E

Product family Hood

Hood Type Decorative wall hood

DesignChimneyExtractionExtractionMaterialHeat-mouldedType of steelBrushed

EAN code 8017709211745

Hood width 90 cm

Aesthetic Cortina

Colour Anthracite

Components finishing Antique brass

Logo Applied



Controls

Control settingControl knobsControl knobsCortinaNo. of controls2Controls colourAnthracite

Program / Functions

No. of speeds Intensive speed



Technical Features



No. of lights 2 No. of filters 3

Light typeLEDAnti-grease filtersAluminiumLight Power1 WVent outlet150 mmLight color temperature3000 KMinimum distance from750 mm

scale (K) GAS hob

Free outlet maximum 820 m³/h Minimum distance from 650 mm

capacity ELECTRIC hob

Motor power 275 W Non return valve Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	326	50
Speed 2	439	57



Speed 3	549	62
Intensive speed	794	71

Performance / Energy Label

	A***
<	Ť

Annual Efficiency 58 kWh/a Airbourne acouistical A- 50 dBA weighted sound Power Consumption (AEChood) **Emission at minimum** Energy efficieency class A speed (SPEmin) (EEC) Airborne acoustical A-62 dBA Fluid Dynamic Efficiency 31,9 weighted sound Power (FDE) **Emission at maximum** Fluid Dynamic Efficiency A speed (SPEmax) class (FDEC) Airbourne acoustical A- 71 dBA Lighting Efficiency (LE) 83,6 lux/W weighted sound power Lighting Efficiency Class A emission at boost speed (LEC) (SPEboost) **Grease Filtering** 77,9 % Time increase factor (F) 0,9 Efficiency (GFE) **Energy Efficiency Index** 53,1 **Grease Filtering** Measured air flow rate 430 m³/h Efficiency Class (GFEC) at best efficiency point Air flow at minumum 326 m³/h (Qbep) speed (Qmin) Measured air pressure 457 Pa Air flow at maximum 549 m³/h at best efficiency point speed (Qmax) (Pbep) Air flow at boost speed 794 m³/h Measured electric 171 W (Qboost) power input at best efficiency point (Wbep) **Nominal Power** 2 W consumption of the light system (WL) Average illumination of 184 lux the light on the cooking

Electrical Connection

Electrical connection 277 W Power supply cable 1000 mm

rating length

Voltage 220-240 V Plug Not present Frequency (Hz) 50-60 Hz

Also available

Alternative colours White, Cream, Copper, Available colours KC19BSE-KC19OTE-available Brass, Red Wine KC19POE-KC19RAE-

KC19RWE


62 dBA

SMEG SPA 27/11/2025

surface (Emiddle) Sound power level at

highest setting (Lwa)







Compatible Accessories

FLT6

Round Charcoal filters (kit 2 pieces)



KITKCX-2



KIT LOGO & HANDRAIL CHROME FINISHING





KIT LOGO CHROME FINISHING



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

KITLOGOAS

SMEG

KIT LOGO ANTIQUE SILVER FINISHING



Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Energy efficiency class A



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.