

# KCI19POE

Product family Hood

Hood Type Decorative island hood

DesignRoundedExtractionExtractionMaterialHeat-mouldedEAN code8017709212490

Hood width 90 cm
Aesthetic Cortina
Colour Cream
Components finishing Antique brass

Logo Applied



## **Controls**

Control settingControl knobsControl knobsCortinaNo. of controls2Controls colourCream

## **Program / Functions**

No. of speeds
Intensive speed

## **Technical Features**



No. of lights 4 No. of filters 3

Light typeLEDAnti-grease filtersAluminiumLight Power1 WVent outlet150 mmLight color temperature3000 KMinimum distance from750 mm

scale (K) GAS hob

Free outlet maximum 820 m³/h Minimum distance from 650 mm

capacity ELECTRIC hob

Motor power 275 W Non return valve Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	321	47
Speed 2	385	59



Speed 3	549	61
Intensive speed	796	70

321 m<sup>3</sup>/h

549 m<sup>3</sup>/h

### Accessories included

Tube reduction Yes

## Performance / Energy Label

A F

Annual Efficiency 59 kWh/a Consumption (AEChood)

Energy efficieency class A

(EEC)

Fluid Dynamic Efficiency 25,9

(FDE)

Fluid Dynamic Efficiency A

class (FDEC)

Lighting Efficiency (LE) 68,6 lux/W

Lighting Efficiency Class  $\, A \,$ 

(LEC)

Grease Filtering 78 %

Efficiency (GFE)

Grease Filtering (
Efficiency Class (GFEC)

Air flow at minumum

Air flow at minumum

speed (Qmin)

Air flow at maximum

speed (Qmax)

Air flow at boost speed 796 m³/h

(Qboost)

Airbourne acouistical A- 47 dBA

weighted sound Power Emission at minimum

speed (SPEmin)

Airborne acoustical A- 61 dBA

weighted sound Power Emission at maximum speed (SPEmax)

Airbourne acoustical A- 70 dBA

weighted sound power emission at boost speed

(SPEboost)

Time increase factor (F) 0,9 Energy Efficiency Index 53,1

Measured air flow rate 426 m³/h

at best efficiency point

(Qbep)

Measured air pressure

at best efficiency point

(Pbep)

Measured electric 170 W

power input at best efficiency point (Wbep)

Nominal Power 4 W consumption of the light

system (WL)

Average illumination of

the light on the cooking

surface (Emiddle)

Sound power level at highest setting (Lwa)

302 lux

453 Pa

61 dBA

1000 mm

## **Electrical Connection**

Electrical connection 279 W

rating

Voltage 220-240 V Frequency (Hz) 50-60 Hz Power supply cable

length

Plug Not present

#### Also available



Alternative colours Anthracite Available colours KCI19AOE available MIN.750 - MAX.1150 \$1/IBC



# **Compatible Accessories**

FLT6

Round Charcoal filters (kit 2 pieces)

SMEG

**KITLOGOAS** 

KIT LOGO ANTIQUE SILVER FINISHING



SMEG

**KITLOGOCR** 

KIT LOGO CHROME FINISHING



# Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Energy efficiency class A



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.