

# KCU94AN

|                      |                                    |
|----------------------|------------------------------------|
| Product family       | Hood                               |
| Hood Type            | Decorative wall hood               |
| Design               | Chimney                            |
| Extraction           | Extraction                         |
| Material             | Stainless Steel + Painted Material |
| Type of steel        | Brushed                            |
| EAN code             | 8017709367855                      |
| Hood width           | 90 cm                              |
| Aesthetic            | Portofino                          |
| Colour               | Anthracite                         |
| Finishing            | Matte                              |
| Components finishing | Stainless steel                    |
| Logo                 | Applied                            |



## Controls



Control setting

Touch control

## Program / Functions

|                 |                                                                                     |
|-----------------|-------------------------------------------------------------------------------------|
| No. of speeds   | 3                                                                                   |
| Intensive speed |  |
| Auto-vent 2.0   |  |
| Auto-vent 2.0   |  |

## Technical Features



|                                   |          |                                    |                 |
|-----------------------------------|----------|------------------------------------|-----------------|
| Buffle filters                    | Yes      | Motor power                        | 275 W           |
| No. of lights                     | 2        | No. of filters                     | 3               |
| Light type                        | LED      | Anti-grease filters                | Stainless steel |
| Light Power                       | 2 W      | Vent outlet                        | 150 mm          |
| Dimmer mode                       | Yes      | Minimum distance from GAS hob      | 750 mm          |
| Light color temperature scale (K) | 4000 K   | Minimum distance from ELECTRIC hob | 650 mm          |
| Free outlet maximum capacity      | 815 m³/h | Non return valve                   | Yes             |

|                    | Extraction rate IEC<br>61591 [m³/h] | Noise level IEC 60704-<br>2-13 [dBA] |
|--------------------|-------------------------------------|--------------------------------------|
| Speed 1            | 237                                 | 43                                   |
| Speed 2            | 403                                 | 56                                   |
| Speed 3            | 577                                 | 64                                   |
| Intensive<br>speed | 741                                 | 70                                   |

## Performance / Energy Label




|                                          |          |
|------------------------------------------|----------|
| Annual Efficiency Consumption (AEChood)  | 34 kWh/a |
| Energy efficiency class (EEC)            | A++      |
| Fluid Dynamic Efficiency (FDE)           | 39.6     |
| Fluid Dynamic Efficiency class (FDEC)    | A        |
| Lighting Efficiency (LE)                 | 33 lux/W |
| Lighting Efficiency Class (LEC)          | A        |
| Grease Filtering Efficiency (GFE)        | 92.6 %   |
| Grease Filtering Efficiency Class (GFEC) | B        |
| Air flow at minumum speed (Qmin)         | 237 m³/h |
| Air flow at maximum speed (Qmax)         | 577 m³/h |
| Air flow at boost speed (Qboost)         | 741 m³/h |

|                                                                                |          |
|--------------------------------------------------------------------------------|----------|
| Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) | 43 dBA   |
| Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)  | 65 dBA   |
| Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost) | 70 dBA   |
| Time increase factor (F)                                                       | 1.00     |
| Energy Efficiency Index                                                        | 40.3     |
| Measured air flow rate at best efficiency point (Qbep)                         | 413 m³/h |
| Measured air pressure at best efficiency point (Pbep)                          | 476 Pa   |
| Measured electric power input at best efficiency point (Wbep)                  | 151 W    |
| Nominal Power consumption of the light system (WL)                             | 2 W      |
| Average illumination of the light on the cooking surface (Emiddle)             | 172 lux  |
| Sound power level at highest setting (Lwa)                                     | 66 dBA   |

## Electrical Connection

|                              |           |                           |         |
|------------------------------|-----------|---------------------------|---------|
| Electrical connection rating | 277 W     | Power supply cable length | 1000 mm |
| Voltage                      | 220-240 V | Plug                      | No      |
| Frequency (Hz)               | 50-60 Hz  |                           |         |

## Also available



---


## Compatible Accessories

---



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



### KITFCGT94

---

## Alternative products

---



**KCU94BL**  
Colour: Black



**KCU94WH**  
Colour: White



**KCU94X**  
Colour: Stainless steel



**KCU94MLM**  
Colour: Moonlight



**KCU94SBM**  
Colour: Storm Blue



**KCU94EGM**  
Colour: Emerald Green



**KCU94ACM**  
Colour: Amber Clay

## Symbols glossary



A++: Energy efficiency class A++ helps to save up to 20% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Touch controls: Easy to use touch controls allow the appliance to be programmed at the touch of a button.



Intensive/turbo setting: when extra fast extraction is required.



Connection between hob and hood



Dimmering Lights



V-Condense System is a system that avoids the drips of condensation that you could show up on the hood within certain circumstance of use.