

KD100XE

Product family	Hood
Hood Type	Decorative wall hood
Design	Chimney
Extraction	Extraction
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709211622
Hood width	100 cm
Aesthetic	Classica
Colour	Stainless steel
Finishing	Satin
Logo	Embossed



Controls

Control setting	Control knobs	Control knobs	Classic
No. of controls	2	Controls colour	Steel effect

Program / Functions

No. of speeds	3
Intensive speed	

Technical Features

			
No. of lights	2	No. of filters	3
Light type	LED	Anti-grease filters	Stainless steel
Light Power	2 W	Vent outlet	150 mm
Light color temperature scale (°K)	4000 °K	Minimum distance from GAS hob	750 mm
Free outlet maximum capacity	820 m³/h	Minimum distance from ELECTRIC hob	650 mm
Motor power	275 W	Non return valve	Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	320	49
Speed 2	439	57

Speed 3	545	62
Intensive speed	773	70

Performance / Energy Label



Annual Efficiency Consumption (AEChood) 57 kWh/a
Energy efficiency class (EEC) A
Fluid Dynamic Efficiency (FDE) 31,6
Fluid Dynamic Efficiency class (FDEC) A
Lighting Efficiency (LE) 85,5 lux/W
Lighting Efficiency Class (LEC) A
Grease Filtering Efficiency (GFE) 74,7 %
Grease Filtering Efficiency Class (GFEC) D
Air flow at minumum speed (Qmin) 320 m³/h
Air flow at maximum speed (Qmax) 545 m³/h
Air flow at boost speed (Qboost) 773 m³/h

Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) 49 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) 62 dBA
Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost) 70 dBA
Time increase factor (F) 1,00
Measured air flow rate at best efficiency point (Qbep) 413 m³/h
Measured air pressure at best efficiency point (Pbep) 460 Pa
Measured electric power input at best efficiency point (Wbep) 167 W
Nominal Power consumption of the light system (WL) 2 W
Average illumination of the light on the cooking surface (Emiddle) 188 lux
Sound power level at highest setting (Lwa) 62 dBA

Electrical Connection

Plug Not present
Electrical connection rating 278 W
Voltage 220-240 V


Frequency (Hz) 50-60 Hz
Power supply cable length 1500 mm

Also available

Alternative colours available Black

Available colours KD100NE

Optional accessories



Compatible Accessories



FLT6

Round Charcoal filters (kit 2 pieces)



KITCMNKD

Chimney extension dimension 202.8 *
276 * 800



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.