

KD70XE

Product family	Hood
Hood Type	Decorative wall hood
Design	Chimney
Extraction	Extraction
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709211585
Hood width	70 cm
Aesthetic	Classica
Colour	Stainless steel
Finishing	Satin
Logo	Embossed



Controls

Control setting	Control knobs	Control knobs	Classic
No. of controls	2	Controls colour	Steel effect

Program / Functions

No. of speeds	3
Intensive speed	

Technical Features



No. of lights	2	No. of filters	2
Light type	LED	Anti-grease filters	Stainless steel
Light Power	2 W	Vent outlet	150 mm
Light color temperature scale (K)	4000 K	Minimum distance from GAS hob	750 mm
Free outlet maximum capacity	820 m ³ /h	Minimum distance from ELECTRIC hob	650 mm
Motor power	275 W	Non return valve	Yes

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	323	50
Speed 2	439	57

Speed 3	542	62
Intensive speed	761	70

Performance / Energy Label


	Annual Efficiency Consumption (AEChood)	63 kWh/a	Airbourne acoustical A- weighted sound Power Emission at minimum speed (SPEmin)	50 dBA
	Energy efficiency class (EEC)	B	Airborne acoustical A- weighted sound Power Emission at maximum speed (SPEmax)	62 dBA
	Fluid Dynamic Efficiency (FDE)	28,5	Airborne acoustical A- weighted sound power emission at boost speed (SPEboost)	70 dBA
	Fluid Dynamic Efficiency class (FDEC)	A	Time increase factor (F)	1,00
	Lighting Efficiency (LE)	111,8 lux/W	Energy Efficiency Index	57,7
	Lighting Efficiency Class (LEC)	A	Measured air flow rate at best efficiency point (Qbep)	394 m³/h
	Grease Filtering Efficiency (GFE)	77,8 %	Measured air pressure at best efficiency point (Pbep)	436 Pa
	Grease Filtering Efficiency Class (GFEC)	C	Measured electric power input at best efficiency point (Wbep)	168 W
	Air flow at minimum speed (Qmin)	323 m³/h	Nominal Power consumption of the light system (WL)	2 W
	Air flow at maximum speed (Qmax)	542 m³/h	Average illumination of the light on the cooking surface (Emiddle)	246 lux
	Air flow at boost speed (Qboost)	761 m³/h	Sound power level at highest setting (Lwa)	62 dBA

Electrical Connection

Electrical connection rating	278 W	Power supply cable length	1500 mm
Voltage	220-240 V	Plug	Not present
Frequency (Hz)	50-60 Hz		

Also available

Alternative colours available	White	Available colours	KD70WHE
--------------------------------------	-------	--------------------------	---------



Compatible Accessories

FLT6

Round Charcoal filters (kit 2 pieces)



KITCMNKD

Chimney extension dimension 202.8 *
276 * 800



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.