

KDD90CNE2



Product family	Hood
Hood Type	Downdraft Cooker Hoods
Design	Fully integrated
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Perimeter extraction	Yes
Material	Painted material
EAN code	8017709346126
Hood width	90 cm
Aesthetics	Universal
Colour	Black
Finishing	Glass
Glass Type	Black
Serigraphy colour	Silver
Logo	Silk screen



Controls



Control setting	Touch control	Display	Digital
Led colour	White		

Program / Functions

No. of speeds	4
Intensive speed	
24h air filter function	
Other functions	Delay_function
Time-setting options	

Technical Features



Remote motor	KITRBDD - Kit Optional	Free outlet maximum capacity	740 m³/h
No. of lights	1	Motor power	250 W
Light type	LED	No. of filters	2
Light power	5 W	Anti-grease filters	Aluminium
Dimmer mode	Yes	Filter replacement indicator	Yes
Light colour temperature scale (K)	4000 K		

Vent outlet

150 mm

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	200	43
Speed 2	280	49
Speed 3	350	53
Speed 4	440	57
Intensive speed	720	68

Accessories Included

Remote control	Optional	Tube reduction	Yes
Sliding door	Yes		

Performance / Energy Label



Annual Efficiency Consumption (AEChood) 57 kWh/year

Energy efficiency class (EEC) A

Fluid Dynamic Efficiency (FDE) 29,30

Fluid Dynamic Efficiency class (FDEC) A

Lighting Efficiency (LE) 40 lux/W

Lighting Efficiency Class (LEC) A

Grease Filtering Efficiency (GFE) 65,1 %

Grease Filtering Efficiency Class (GFEC) D

Air flow at minumum speed (Qmin) 200 m³/h

Maximum extraction rate 350 m³/h

Intensive extraction rate 720 m³/h

Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) 43 dBA

Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) 53 dBA

Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost) 68 dBA

Time increase factor (F) 0,9

Energy Efficiency Index per first cavity 53,1

Measured air flow rate at best efficiency point (Qbep) 398 m³/h

Measured air pressure at best efficiency point (Qbep) 429 Pa

Measured electric power input at best efficiency point (Wbep) 162 W

Normal Power of the light system (WI) 5 W

Average illumination of the light on the cooking surface (Emiddle) 200 lux


Sound power level at highest setting (Lwa) 49 dBA

Electrical Connection

Nominal power	255 W	Power supply cable length	1500 mm
Voltage	220-240 V	Plug	(F;E) Schuko
Frequency (Hz)	50-60 Hz		

Also available

Alternative colours available White, Silver Glass



Compatible Accessories



KITFCDD

Charcoal filter for hood Down Draft Kit 1 piece Dishwasher safe














RCKF2

Remote control

KITRBDD

kit remote blower for DD hood

Symbols glossary

	24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.		A: Product drying performance, measured from A+++ to D / G depending on the product family
	Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.		Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.
	Electronic display: to give a visual reminder of the options selected.		Warning light(s): to advise when filters need changing.
	Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.		Perimeter extraction panels: very efficient and aid noise reduction.
	Touch controls: Easy to use touch controls allow the appliance to be programmed at the touch of a button.		Intensive/turbo setting: when extra fast extraction is required.
	...		