

KDE900EX

Product family

Hood Type Decorative wall hood

Hood

Design Chimney Extraction Extraction Material Stainless steel Type of steel Brushed

EAN code 8017709235161

Hood width 90 cm



Aesthetics

Universale Components finishing **Aesthetic** Stainless steel Stainless steel Serigraphy colour Colour Black

Finishing Satin Silk screen Logo

Controls

Control setting **Buttons**

Program / Functions

3 No. of speeds

180 W

Technical Features

No. of lights No. of filters

Light type LED Anti-grease filters Aluminium **Light Power** 3 W Vent outlet 150 mm 700 mm

Light color temperature 2700 °K Minimum distance from GAS hob scale (°K)

Free outlet maximum 588 m³/h Minimum distance from 500 mm

capacity **ELECTRIC hob**

Motor power Non return valve Yes



	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2- 13 [dBA]
Speed 1	202	42
Speed 2	307	52
Speed 3	553	65

Accessories Included

Tube reduction Yes

Performance / Energy Label

D †

Annual Efficiency 103 kWh/a Airbo
Consumption (AEChood) weigh
Energy efficiency class D
Emiss
(EEC) Speed
Fluid Dynamic Efficiency 12,6
(FDE) Airbo

Fluid Dynamic Efficiency E class (FDEC)

Lighting Efficiency (LE) 16,1 lux/W

Lighting Efficiency Class C (LEC)

Grease Filtering 76 % Efficiency (GFE)

Grease Filtering C
Efficiency Class (GFEC)

Air flow at minumum 208 m³/h

speed (Qmin)

Air flow at maximum 559 m³/h speed (Qmax)

Airbourne acouistical A- 44 dBA

weighted sound Power Emission at minimum speed (SPEmin)

Airborne acoustical A- 67 dBA weighted sound Power Emission at maximum speed (SPEmax)

Time increase factor (F) 1,5

Measured air flow rate 320 m³/h

at best efficiency point (Qbep)

Measured air pressure at best efficiency point

(Pbep)
Measured electric 180 W

power input at best efficiency point (Wbep)

Nominal Power 6 W consumption of the light

system (WL)

Average illumination of 97 lux

the light on the cooking surface (Emiddle)

Sound power level at highest setting (Lwa)

67 dBA

255 Pa

Electrical Connection

Plug Not present Frequency (Hz)
Electrical connection 186 W Power supply c

rating Voltage 220-240 V


Frequency (Hz) 50-60 Hz Power supply cable 1500 mm length



Optional accessories

Charcoal filter

KITFC450





Not included accessories

KITFC450

Charcoal filters ROUND Kit 2 pieces KDE600XE KDE900XE





Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.

