

KDH12WLD



Product family	Hood
Hood Type	Downdraft Cooker Hoods
Design	Fully integrated
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Perimeter extraction	Yes
Material	Glass
EAN code	8017709277826
Hood width	
Aesthetics	Universal
Colour	Black
Finishing	Glass
Glass Type	ceramic Eclipse
Serigraphy colour	White
Logo	Silk screen



Controls



Control setting	Touch control	Display	Digital
Led colour	Ice		

Program / Functions

No. of speeds	3
Intensive speed	
Time-setting options	

Technical Features



Free outlet maximum capacity	570 m³/h	Anti-grease filters	Stainless steel
Motor power	145 W	Filter replacement indicator	Yes
No. of filters	1		

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	370	62
Speed 2	420	66

Speed 3	470	69
Intensive speed	550	72

Accessories Included

Sliding door	Yes
--------------	-----

Performance / Energy Label



Annual Efficiency Consumption (AEChood) 37 KWh/year

Energy efficiency class (EEC) A+

Fluid Dynamic Efficiency (FDE) 32

Fluid Dynamic Efficiency class (FDEC) A

Lighting Efficiency Class (LEC) NA

Grease Filtering Efficiency (GFE) 75,1 %

Grease Filtering Efficiency Class (GFEC) C

Air flow at minumum speed (Qmin) 370 m³/h

Maximum extraction rate 470 m³/h

Intensive extraction rate 550 m³/h

Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin) 62 dBA

Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) 69 dBA

Airbourne acouistical A-weighted sound power emission at boost speed (SPEboost) 72 dBA

Time increase factor (F) 0,8

Energy Efficiency Index per first cavity 43,4

Measured air flow rate at best efficiency point (Qbep) 295 m³/h

Measured air pressure at best efficiency point (Qbep) 490 Pa

Measured electric power input at best efficiency point (Wbep) 125 W

Sound power level at highest setting (Lwa) 72 dBA

Electrical Connection

Nominal power 145 W
Voltage 220-240 V

Frequency (Hz) 50-60 Hz
Power supply cable length 1500 mm

Compatible Accessories



CFKDH12HP

Ceramic filter for Domino Hood KDH12WLD Kit 1 piece High performances. Regenerable into oven Magnetic Metallic grid included.



FLMSTPKDH12

Metallic flame guard hob aspiration hood Kit 1 piece


GRIDKDH12

Metallic grid for standard charcoal filter hob aspiration hood Kit 1 piece



CFKDH12STD









Charcoal filter for hob aspiration hood Kit 1 piece



FLTKDH

Anti-Odour Filter Ceramic regenerative suitable for Recirculating kit (accessory CFKDH12HP)

Symbols glossary

	Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.		Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.
	A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.		Electronic display: to give a visual reminder of the options selected.
	Warning light(s): to advise when filters need changing.		Perimeter extraction panels: very efficient and aid noise reduction.
	Touch controls: Easy to use touch controls allow the appliance to be programmed at the touch of a button.		Intensive/turbo setting: when extra fast extraction is required.

Benefit

Dimmering & Tunable lights

Customisable LED lighting lets you adjust both the intensity and colour temperature, from warm to cool tones, so you can create the perfect lighting for any mood or task

Perimetral aspiration

Enhanced extraction with a perimeter aspiration system ensures optimised performance, for a cleaner, fresher kitchen

Perimeter aspiration enhances extraction efficiency by directing vapors along the edges of the panel beneath the filters, optimizing air capture