KDIAM120AX



Product family	Hood
Hood Type	Integrated hood
Design	Fully integrated
Extraction	Extraction
Electronic control	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709328405
Hood width	120 cm
Aesthetic	Universale
Colour	Stainless steel
Finishing	Satin
Logo	Embossed

Controls

Control setting	Electronic buttons	**Led color**	White

Program / Functions

No. of speeds	3
Intensive speed	BOOST
Time-setting options	

Technical Features

No. of lights	4	**Anti-grease filters**	Buffle
Light type	LED	**Filter replacement indicator**	Yes
Light Power	1 W	**Vent outlet**	150 mm
Light color temperature scale (K)	3000 K	**Minimum distance from GAS hob**	750 mm
Free outlet maximum capacity	1400 m³/h	**Minimum distance from ELECTRIC hob**	650 mm
Motor power	550 W	**Non return valve**	Yes
No. of filters	3		


	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	552	46

Speed 2	950	63
Speed 3	1412	71
Intensive speed	1555	74

Electrical Connection

Electrical connection rating	555 W	**Power supply cable length**	1500 mm
Voltage	220-240 V	**Plug**	(I) Australia
Frequency (Hz)	50-60 Hz		

Compatible Accessories



AIRKITDIAM

air conveyor kit from the two hood motors in a single outlet with a diameter of 200 mm (the motors come out at 150 mm)



FLT6

Round Charcoal filters (kit 2 pieces)

Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Warning light(s): to advise when filters need changing.



Intensive/turbo setting: when extra fast extraction is required.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.