

KDIAM120AX

Product family Hood

Hood Type Integrated hood Fully integrated Design Extraction Extraction

Electronic control Yes

Material Stainless steel Type of steel Brushed

EAN code 8017709328405

Hood width 120 cm **Aesthetic** Universale Colour Stainless steel

Finishing Satin Logo **Embossed**



Controls

Control setting **Electronic buttons** Led color White

Program / Functions

No. of speeds Intensive speed

Time-setting options





Technical Features







No. of lights 4 Anti-grease filters Buffle LED Filter replacement Light type Yes

1 W **Light Power**

Light color temperature 3000 K scale (K)

Free outlet maximum

1400 m³/h

capacity

Motor power 550 W No. of filters 3

indicator Vent outlet 150 mm 750 mm

Minimum distance from GAS hob

Minimum distance from

ELECTRIC hob

650 mm

Non return valve Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	552	46

SMEG SPA 28/11/2025



Speed 2	950	63
Speed 3	1412	71
Intensive speed	1555	74

Electrical Connection

Electrical connection

555 W

Power supply cable length

1500 mm

rating Voltage

220-240 V

Plug

(I) Australia

Frequency (Hz) 50-60 Hz

SMEG SPA 28/11/2025



Compatible Accessories

AIRKITDIAM



air conveyor kit from the two hood motors in a single outlet with a diameter of 200 mm (the motors come out at 150 mm)

FLT6





SMEG SPA 28/11/2025



Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Warning light(s): to advise when filters need changing.



Intensive/turbo setting: when extra fast extraction is required.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.

SMEG SPA 28/11/2025