KDIAM90AX

Product family	Hood
Hood Type	Canopy Cooker Hoods
Design	Fully integrated
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709217082
Hood width	90 cm
Aesthetics	Universal
Colour	Stainless steel
Finishing	Brushed
Logo	Embossed



Controls

Control setting	Electronic buttons	**Led colour**	White

Program / Functions

No. of speeds	3
Intensive speed	BOOST
Time-setting options	

Technical Features


No. of lights	4	**Anti-grease filters**	Buffle
Light type	LED	**Filter replacement indicator**	Yes
Light power	1 W	**Vent outlet**	150 mm
Light colour temperature scale (K)	3000 K	**Minimum distance from GAS hob**	750 mm
Free outlet maximum capacity	1400 m³/h	**Minimum distance from ELECTRIC hob**	650 mm
Motor power	550 W	**Non return valve**	Yes
No. of filters	2		

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	552	46


Speed 2	950	63
Speed 3	1412	71
Intensive speed	1555	74

Electrical Connection

Nominal power	555 W	**Power supply cable length**	1500 mm
Voltage	220-240 V	**Plug**	(I) Australia
Frequency (Hz)	50-60 Hz		



Compatible Accessories



AIRKITDIAM

air conveyor kit from the two hood motors in a single outlet with a diameter of 200 mm (the motors come out at 150 mm)



FLT6

Round Charcoal filters (kit 2 pieces)

Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Warning light(s): to advise when filters need changing.



Intensive/turbo setting: when extra fast extraction is required.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.