

# KDIAM90X

|                    |                  |
|--------------------|------------------|
| Product family     | Hood             |
| Hood Type          | Integrated hood  |
| Design             | Fully integrated |
| Extraction         | Extraction       |
| Electronic control | Yes              |
| Material           | Stainless steel  |
| Type of steel      | Brushed          |
| EAN code           | 8017709253851    |
| Hood width         | 90 cm            |
| Aesthetic          | Universale       |
| Colour             | Stainless steel  |
| Finishing          | Satin            |
| Logo               | Embossed         |




## Controls

|                 |                    |           |       |
|-----------------|--------------------|-----------|-------|
| Control setting | Electronic buttons | Led color | White |
|-----------------|--------------------|-----------|-------|

## Program / Functions

|                      |   |
|----------------------|---|
| No. of speeds        | 3   |
| Intensive speed      |  |
| Time-setting options |  |

## Technical Features




|                                   |                        |                                    |        |
|-----------------------------------|------------------------|------------------------------------|--------|
| No. of lights                     | 4                      | Anti-grease filters                | Baffle |
| Light type                        | LED                    | Filter replacement indicator       | Yes    |
| Light Power                       | 1 W                    | Vent outlet                        | 150 mm |
| Light color temperature scale (K) | 3000 K                 | Minimum distance from GAS hob      | 650 mm |
| Free outlet maximum capacity      | 1400 m <sup>3</sup> /h | Minimum distance from ELECTRIC hob | 750 mm |
| Motor power                       | 550 W                  | Non return valve                   | Yes    |
| No. of filters                    | 2                      |                                    |        |

|         | Extraction rate IEC 61591 [m <sup>3</sup> /h] | Noise level IEC 60704-2-13 [dBA] |
|---------|---|----------------------------------|
| Speed 1 | 552   | 46                               |

|                 |      |    |
|-----------------|------|----|
| Speed 2         | 950  | 63 |
| Speed 3         | 1412 | 71 |
| Intensive speed | 1555 | 74 |

## Electrical Connection

|                              |           |                           |         |
|------------------------------|-----------|---------------------------|---------|
| Electrical connection rating | 555 W     | Power supply cable length | 1500 mm |
| Voltage                      | 220-240 V | Plug                      | No      |
| Frequency (Hz)               | 50-60 Hz  |                           |         |




---

## Compatible Accessories

---

### AIRKITDIAM



air conveyor kit from the two hood motors in a single outlet with a diameter of 200 mm (the motors come out at 150 mm)

### FLT6



Round Charcoal filters (kit 2 pieces)

---

## Symbols glossary

---

- |  |   |   |  |
|--|---|---|--|
|  | Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking. |  | Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically. |
|  | Warning light(s): to advise when filters need changing.   |  | Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.                      |
|  | Intensive/turbo setting: when extra fast extraction is required.  |   |  |