

# KDIAM90X

Product family	Hood
Hood Type	Integrated hood
Design	Fully integrated
Extraction	Extraction
Electronic control	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709253851
Hood width	90 cm



## Aesthetics

Aesthetic	Universale	Finishing	Satin
Colour	Stainless steel	Logo	Embossed

## Controls

Control setting	Electronic buttons	Led color	White
-----------------	--------------------	-----------	-------

## Programs / Functions

No. of speeds	3
Intensive speed	
Time-setting options	

## Technical Features





No. of lights	4	Anti-grease filters	Buffle
Light type	LED	Filter replacement indicator	Yes
Light Power	1 W	Vent outlet	150 mm
Light color temperature scale (°K)	3000 °K	Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	1400 m³/h	Minimum distance from ELECTRIC hob	750 mm
Motor power	550 W		

No. of filters 2 Non return valve Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	552	46
Speed 2	950	63
Speed 3	1412	71
Intensive speed	1555	74

## Electrical Connection

Electrical connection rating 555 W Frequency (Hz) 50-60 Hz  
Voltage 220-240 V Power supply cable length 1500 mm



---

## Not included accessories

---



### FLT6

Round Charcoal filters (kit 2 pieces)

### AIRKITDIAM

air conveyor kit from the two hood motors in a single outlet with a diameter of 200 mm (the motors come out at 150 mm)

---

## Symbols glossary (TT)

---



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Warning light(s): to advise when filters need changing.



Intensive/turbo setting: when extra fast extraction is required.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.