

KFAB75RD

Product family	Hood
Hood Type	Decorative wall hood
Design	Angled
Extraction	Recirculation
Electronic control	Yes
Material	Painted material
Type of steel	Brushed
EAN code	8017709224882
Hood width	75 cm
Aesthetic	50's Style
Colour	Red
Finishing	Glossy
Logo	Applied




Controls

Control setting	Electronic buttons	Led color	White
-----------------	--------------------	-----------	-------

Program / Functions

No. of speeds	3
Intensive speed	
Time-setting options	

Technical Features



No. of lights	2	Anti-grease filters	Stainless steel
Light type	LED	Charcoal filters included	Yes
Light Power	1 W	Filter replacement indicator	Yes
Light color temperature scale (K)	4000 K	Vent outlet	150 mm
Free outlet maximum capacity	820 m ³ /h	Minimum distance from GAS hob	650 mm
Motor power	280 W	Minimum distance from ELECTRIC hob	650 mm
No. of filters	3	Non return valve	Yes

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	333	50

Speed 2	477	59
Speed 3	649	67
Intensive speed	797	72

Accessories included

Remote control	Yes	Motorised opening	Yes
----------------	-----	-------------------	-----

Performance / Energy Label

			
Annual Efficiency Consumption (AEChood)	36 kWh/a	Airbourne acoustical A- weighted sound Power	50 dBA
Energy efficiency class (EEC)	A+	Emission at minimum speed (SPEmin)	
Fluid Dynamic Efficiency (FDE)	36.6	Airborne acoustical A- weighted sound Power	67 dBA
Fluid Dynamic Efficiency class (FDEC)	A	Emission at maximum speed (SPEmax)	
Lighting Efficiency (LE)	68.2 lux/W	Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost)	72 dBA
Lighting Efficiency Class (LEC)	A	Time increase factor (F)	0.7
Grease Filtering Efficiency (GFE)	61.1 %	Energy Efficiency Index	39.7
Grease Filtering Efficiency Class (GFEC)	E	Measured air flow rate at best efficiency point (Qbep)	421 m³/h
Air flow at minimum speed (Qmin)	333 m³/h	Measured air pressure at best efficiency point (Pbep)	422 Pa
Air flow at maximum speed (Qmax)	649 m³/h	Measured electric power input at best efficiency point (Wbep)	135 W
Air flow at boost speed (Qboost)	797 m³/h	Nominal Power consumption of the light system (WL)	2 W
		Average illumination of the light on the cooking surface (Emiddle)	150 lux
		Sound power level at highest setting (Lwa)	67 dBA

Electrical Connection

Battery type	Alkaline-Manganese Dioxide (Zn/MnO ₂)	Frequency (Hz)	50-60 Hz
Electrical connection rating	282 W	Power supply cable length	1500 mm

Current 1 A
Voltage 220-240 V




Also available

Alternative colours available

White, Black, Cream, Blue

Available colours

KFAB75WH-KFAB75BL-
KFAB75CR-KFAB75UJ



Compatible Accessories

FLTSI

Charcoal filters Kit 2 pieces



KITCMNFABRD

Chimneys (2 pieces) Dimensions 550
min. 1035 max. (263x257) For
KFAB75RD Red



Symbols glossary

 A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.	 Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.
 Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.	 Charcoal filters: Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.
 Warning light(s): to advise when filters need changing.	 Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.
 Intensive/turbo setting: when extra fast extraction is required.	