

# KI120XE

Product family	Hood
Hood Type	Island Cooker Hoods
Design	T flat
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709204051
Hood width	120 cm
Aesthetics	Universal
Colour	Stainless steel
Finishing	Brushed
Logo	Embossed



## Controls

Control setting	Electronic buttons	Led colour	White
-----------------	--------------------	------------	-------

## Program / Functions

No. of speeds	3
Intensive speed	
Time-setting options	

## Technical Features

				
No. of lights	4	Anti-grease filters	Aluminium	
Light type	LED	Filter replacement indicator	Yes	
Light power	1 W	Vent outlet	150 mm	
Light colour	4000 K	Minimum distance from GAS hob	750 mm	
temperature scale (K)		Minimum distance from ELECTRIC hob	650 mm	
Free outlet maximum capacity	820 m³/h	Non return valve	Yes	
Motor power	275 W			
No. of filters	4			

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	316	48

Speed 2	385	59
Speed 3	529	62
Intensive speed	783	70

## Accessories Included

Tube reduction Yes

## Performance / Energy Label



Annual Efficiency Consumption (AEC<sub>hood</sub>) 64 kWh/year

Energy efficiency class (EEC) B

Fluid Dynamic Efficiency (FDE) 28,7

Fluid Dynamic Efficiency class (FDEC) A

Lighting Efficiency (LE) 70,9 lux/W

Lighting Efficiency Class (LEC) A

Grease Filtering Efficiency (GFE) 79,8 %

Grease Filtering Efficiency Class (GFEC) C

Air flow at mininum speed (Q<sub>min</sub>) 316 m<sup>3</sup>/h

Maximum extraction rate 529 m<sup>3</sup>/h

Intensive extraction rate 783 m<sup>3</sup>/h

Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPE<sub>min</sub>) 48 dBA

Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE<sub>max</sub>) 62 dBA

Airbourne acoustical A-weighted sound power emission at boost speed (SPE<sub>boost</sub>) 70 dBA

Time increase factor (F) 1,00

Energy Efficiency Index per first cavity 58,7

Measured air flow rate at best efficiency point (Q<sub>bep</sub>) 394 m<sup>3</sup>/h

Measured air pressure at best efficiency point (Q<sub>bep</sub>) 449 Pa

Measured electric power input at best efficiency point (W<sub>bep</sub>) 171 W

Normal Power of the light system (W<sub>I</sub>) 4 W

Average illumination of the light on the cooking surface (E<sub>middle</sub>) 312 lux

Sound power level at highest setting (L<sub>wa</sub>) 62 dBA

## Electrical Connection

Nominal power 279 W  
Voltage 220-240 V

Frequency (Hz) 50-60 Hz  
Power supply cable length 1500 mm



---

## Compatible Accessories

---



### FLT6

Round Charcoal filters (kit 2 pieces)



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary

---



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Warning light(s): to advise when filters need changing.



Intensive/turbo setting: when extra fast extraction is required.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.

