

KI52E3

Product family	Hood
Tipo de Exaustor	Integrated hood
Design	Fully integrated
Extraction	Extraction
Electronic control	No
Perimeter extraction	No
Material	Painted material
EAN code	8017709304362
Aesthetic	Universal
Colour	Silver
Cor da serigrafia	Serigrafia em preto
Logotipo	Logotipo serigrafado



Controls

Control setting	Slider
-----------------	--------

Program / Functions

No. of speeds	3
Intensive speed	No
24h air filter function	No
Other functions	No
Time-setting options	No
Other options	No
Ventilação automática	No
Ventilação automática 2.0	No
Ventilação automática 2.0	No

Technical Features

			
Hood without motor	No	No. of filters	1
Remote motor	No	Anti-grease filters	Aluminium
No. of lights	2	Charcoal filters included	No
Light type	LED	Filter replacement indicator	No
Light Power	4 W	Vent outlet	150 mm
Dimmer mode	No	Minimum distance from GAS hob	650 mm
Escala de temperatura de cor clara (°K)	3000 °K		

Free outlet maximum capacity	350 m³/h	Minimum distance from ELECTRIC hob	500 mm
Motor power	115 W	Non return valve	No

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	160	54
Speed 2	220	59
Speed 3	335	66

Accessories Included

Remote control	No	Tube reduction	Yes
Sliding door	No		


Performance / Energy Label



Consumo anual de energia (CAE exaustor)	59 kWh/a	Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)	54 dBA
Energy efficiency class (EEC)	C	Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)	66 dBA
Fluid Dynamic Efficiency (FDE)	13,1	Time increase factor (F)	1,5
Fluid Dynamic Efficiency class (FDEC)	D	Energy Efficiency Index	80,6
Lighting Efficiency (LE)	13 lux/W	Measured air flow rate at best efficiency point (Qbep)	153 m³/h
Lighting Efficiency Class (LEC)	D	Measured air pressure at best efficiency point (Pbep)	196 Pa
Grease Filtering Efficiency (GFE)	75,1 %	Measured electric power input at best efficiency point (Wbep)	103 W
Grease Filtering Efficiency Class (GFEC)	C	Nominal Power consumption of the light system (WL)	8 W
Air flow at minumum speed (Qmin)	160 m³/h	Average illumination of the light on the cooking surface (Emiddle)	100 lux
Air flow at maximum speed (Qmax)	335 m³/h	Sound power level at highest setting (Lwa)	66 dBA

Electrical Connection

Plug	REINO UNIDO 13 AMP	Frequency (Hz)	50 Hz
Electrical connection rating	103 W	Comprimento do cabo de alimentação	1000 mm
Voltage	220-240 V		



Compatible Accessories

KITFC6191

Filtro de carvão redondo (kit 2 peças)



Symbols glossary



Filtros: O modelo tem filtros para ajudar a remover a graxa do vapor que emana das panelas durante o cozimento.



Luzes: Todos os exaustores possuem luzes para iluminar a área de cozinhar ou adicionar ao ambiente da cozinha.

