

# KI90XE

Product family	Hood
Hood Type	Island Cooker Hoods
Design	T flat
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709204044
Hood width	90 cm
Aesthetics	Universal
Colour	Stainless steel
Finishing	Brushed
Logo	Embossed



## Controls

Control setting	Electronic buttons	Led colour	White
-----------------	--------------------	------------	-------

## Program / Functions

No. of speeds	3
Intensive speed	
Time-setting options	

## Technical Features



No. of lights	4	Anti-grease filters	Aluminium
Light type	LED	Filter replacement indicator	Yes
Light power	1 W	Vent outlet	150 mm
Light colour	4000 K	Minimum distance from GAS hob	750 mm
temperature scale (K)		Minimum distance from ELECTRIC hob	650 mm
Free outlet maximum capacity	820 m³/h	Non return valve	Yes
Motor power	275 W		
No. of filters	3		

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	311	49

Speed 2	385	59
Speed 3	533	63
Intensive speed	740	71

## Accessories Included

Tube reduction	Yes
----------------	-----

## Performance / Energy Label



Annual Efficiency Consumption (AEChood) 66 kWh/year

Energy efficiency class (EEC) B

Fluid Dynamic Efficiency (FDE) 27.4

Fluid Dynamic Efficiency class (FDEC) B

Lighting Efficiency (LE) 88.6 lux/W

Lighting Efficiency Class (LEC) A

Grease Filtering Efficiency (GFE) 83.1 %

Grease Filtering Efficiency Class (GFEC) C

Air flow at minumum speed (Qmin) 311 m³/h

Maximum extraction rate 533 m³/h

Intensive extraction rate 740 m³/h

Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin) 49 dBA

Airborne acouistical A-weighted sound Power Emission at maximum speed (SPEmax) 63 dBA

Airbourne acouistical A-weighted sound power emission at boost speed (SPEboost) 71 dBA

Energy Efficiency Index per first cavity 58.8

Measured air flow rate at best efficiency point (Qbep) 390 m³/h

Measured air pressure at best efficiency point (Qbep) 451 Pa

Measured electric power input at best efficiency point (Wbep) 171 W

Normal Power of the light system (WI) 4 W


Average illumination of the light on the cooking surface (Emiddle) 390 lux

Sound power level at highest setting (Lwa) 63 dBA

## Electrical Connection

Nominal power 279 W  
Voltage 220-240 V

Frequency (Hz) 50-60 Hz  
Power supply cable length 1500 mm



---

## Compatible Accessories

---



### FLT6

Round Charcoal filters (kit 2 pieces)



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary

---



**Filters:** Model has filters to help remove grease from the steam emanating from the pans during cooking.



**Lights:** All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



**Switch off automatically:** A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



**Warning light(s):** to advise when filters need changing.



**Intensive/turbo setting:** when extra fast extraction is required.