

KI90XE

Product family

Hood
Island Cooker Hoods

Design
T flat

Extraction
Ducted out or re-circulation possible

Electronic control
Yes

Material
Stainless steel

Type of steel
Brushed

EAN code
8017709204044

Hood width
90 cm

Aesthetics
Universal

Colour
Stainless steel

Finishing
Brushed

Logo
Embossed



Controls

Control setting

Electronic buttons

Led colour

White

Program / Functions

No. of speeds

3


Intensive speed



Time-setting options



Technical Features



No. of lights

4

Anti-grease filters

Aluminium

Light type

LED

Filter replacement indicator

Yes

Light power

1 W

Vent outlet

150 mm

Light colour

4000 K

Minimum distance from GAS hob

750 mm

temperature scale (K)

820 m³/h

Minimum distance from ELECTRIC hob

650 mm

Free outlet maximum capacity

275 W

Non return valve

Yes

Motor power

3

No. of filters

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	311	49

Speed 2	385	59
Speed 3	533	63
Intensive speed	740	71

Accessories Included

Tube reduction Yes


Performance / Energy Label



Annual Efficiency Consumption (AEChood)	66 kWh/year	Airbourne acoustical A- weighted sound Power	49 dBA
Energy efficiency class (EEC)	B	Emission at minimum speed (SPEmin)	
Fluid Dynamic Efficiency (FDE)	27,4	Airborne acoustical A- weighted sound Power	63 dBA
Fluid Dynamic Efficiency class (FDEC)	B	Emission at maximum speed (SPEmax)	
Lighting Efficiency (LE)	88,6 lux/W	Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost)	71 dBA
Lighting Efficiency Class (LEC)	A	Energy Efficiency Index per first cavity	58,8
Grease Filtering Efficiency (GFE)	83,1 %	Measured air flow rate at best efficiency point (Qbep)	390 m³/h
Grease Filtering Efficiency Class (GFEC)	C	Measured air pressure at best efficiency point (Qbep)	451 Pa
Air flow at minimum speed (Qmin)	311 m³/h	Measured electric power input at best efficiency point (Wbep)	171 W
Maximum extraction rate	533 m³/h	Normal Power of the light system (WI)	4 W
Intensive extraction rate	740 m³/h	Average illumination of the light on the cooking surface (Emiddle)	390 lux
		Sound power level at highest setting (Lwa)	63 dBA

Electrical Connection

Nominal power	279 W	Power supply cable length	1500 mm
Voltage	220-240 V	Plug	No
Frequency (Hz)	50-60 Hz		



Compatible Accessories

FLT6

Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Warning light(s): to advise when filters need changing.



Intensive/turbo setting: when extra fast extraction is required.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.

