

KI90XE

Product family	Hood
Hood Type	Decorative island hood
Design	T flat
Extraction	Extraction
Electronic control	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709204044
Hood width	90 cm



Aesthetics

Aesthetic	Universale	Finishing	Satin
Colour	Stainless steel	Logo	Embossed

Controls

Control setting	Electronic buttons	Led color	White
-----------------	--------------------	-----------	-------

Programme / Functions

No. of speeds	3
Intensive speed	
Time-setting options	

Technical Features

			No. of lights	4	Anti-grease filters	Aluminium
			Light type	LED	Filter replacement indicator	Yes
			Light Power	1 W	Vent outlet	150 mm
			Light color temperature scale (°K)	4000 °K	Minimum distance from GAS hob	750 mm
			Free outlet maximum capacity	820 m³/h	Minimum distance from ELECTRIC hob	650 mm
			Motor power	275 W		

No. of filters 3 Non return valve Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	311	49
Speed 2	385	59
Speed 3	533	63
Intensive speed	740	71

Accessories Included

Tube reduction Yes


Performance / Energy Label

B

Annual Efficiency Consumption (AEChood) 66 kWh/a
 Energy efficiency class (EEC) B
 Fluid Dynamic Efficiency (FDE) 27,4
 Fluid Dynamic Efficiency class (FDEC) B
 Lighting Efficiency (LE) 88,6 lux/W
 Lighting Efficiency Class (LEC) A
 Grease Filtering Efficiency (GFE) 83,1 %
 Grease Filtering Efficiency Class (GFEC) C
 Air flow at minumum speed (Qmin) 311 m³/h
 Air flow at maximum speed (Qmax) 533 m³/h
 Air flow at boost speed (Qboost) 740 m³/h

Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) 49 dB(A)
 Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) 63 dB(A)
 Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost) 71 dB(A)
 Power consumption in stand-by mode (Ps) 0,49 W
 Energy Efficiency Index 58,8
 Measured air flow rate at best efficiency point (Qbep) 390 m³/h
 Measured air pressure at best efficiency point (Pbep) 451 Pa
 Measured electric power input at best efficiency point (Wbep) 171 W
 Nominal Power consumption of the light system (WL) 4 W
 Average illumination of the light on the cooking surface (Emiddle) 390 lux
 Sound power level at highest setting (Lwa) 63 dB(A)

Electrical Connection



Not included accessories



FLT6

Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

Symbols glossary (TT)



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



B: Product energy rating, measured from A+++ to D / G depending on the product family.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.