

KICT90BL

Product family	Hood
Hood Type	Decorative wall hood
Design	T flat
Extraction	Extraction
Electronic control	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709262181
Aesthetic	Universale
Colour	Stainless steel
Finishing	Satin
Glass Type	Black
Logo	Embossed



Controls







Control setting

Touch control

Led color

Red

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	
Auto-Vent	

Technical Features



No. of lights	2	Anti-grease filters	Stainless steel
Light type	LED	Filter replacement indicator	Yes
Light Power	1 W	Vent outlet	150 mm
Free outlet maximum capacity	725 m³/h	Minimum distance from GAS hob	650 mm
Motor power	270 W	Minimum distance from ELECTRIC hob	500 mm
No. of filters	3		

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	300	52
Speed 2	420	59
Speed 3	580	66
Intensive speed	700	69

Accessories Included

Tube reduction Yes

Performance / Energy Label




Annual Efficiency Consumption (AEChood) 42 kWh/a
Energy efficiency class (EEC) A+
Fluid Dynamic Efficiency (FDE) 35
Fluid Dynamic Efficiency class (FDEC) A
Lighting Efficiency (LE) 91 lux/W
Lighting Efficiency Class (LEC) A
Grease Filtering Efficiency (GFE) 75,1 %
Grease Filtering Efficiency Class (GFEC) C
Air flow at minumum speed (Qmin) 300 m³/h
Air flow at maximum speed (Qmax) 580 m³/h
Air flow at boost speed (Qboost) 700 m³/h

Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) 52 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) 66 dBA
Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost) 69 dBA
Time increase factor (F) 0,7
Energy Efficiency Index 40,5
Measured air flow rate at best efficiency point (Qbep) 428 m³/h
Measured air pressure at best efficiency point (Pbep) 461 Pa
Measured electric power input at best efficiency point (Wbep) 157 W
Nominal Power consumption of the light system (WL) 2 W
Average illumination of the light on the cooking surface (Emiddle) 200 lux
Sound power level at highest setting (Lwa) 66 dBA

Electrical Connection

Frequency (Hz) 50-60 Hz

Power supply cable length	1500 mm
---------------------------	---------



Compatible Accessories



KITFC161

Charcoal filters Kit 2 pieces



KITVENT150

Imbocco motore 150 mm con valvola di non ritorno

Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



A smart infrared system, which allows a hood and hob with this feature to work together.



A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.



Warning light(s): to advise when filters need changing.



Touch controls: Easy to use touch controls allow the appliance to be programmed at the touch of a button.