

KLT9L4X



Product family	Hood
Hood Type	Ceiling Cooker Hoods
Design	Ceiling
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Perimeter extraction	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709326227
Hood width	90 cm







Aesthetics

Aesthetics	Universal	Finishing	Brushed
Colour	Stainless steel	Logo	Silk screen

Controls

Control setting	Touch control back-lighted White
------------------------	-------------------------------------

Programs / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	
Auto-Vent 2.0	

Technical Features

			
No. of lights	2	No. of filters	3
Light type	LED	Anti-grease filters	Aluminium
Light power	7.4 W		

Light colour temperature scale (°K)	3000 °K	Filter replacement indicator	Yes
Light colour temperature range	3000° - 5700° °K	Vent outlet	150 mm
Free outlet maximum capacity	610 m ³ /h	Minimum distance from GAS hob	650 mm
Motor power	270 W	Minimum distance from ELECTRIC hob	650 mm
		Non return valve	Yes

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	208	48
Speed 2	323	55
Speed 3	452	62
Intensive speed	594	69

Accessories Included

Remote control	Yes
----------------	-----

Performance / Energy Label




Annual Efficiency Consumption (AEChood)	94 KWh/year	Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)	63 dBA
Energy efficiency class (EEC)	B	Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)	69 dBA
Fluid Dynamic Efficiency (FDE)	25,9	Power consumption in stand-by mode (Ps)	0,49 W
Fluid Dynamic Efficiency class (FDEC)	B	Time increase factor (F)	1,1
Lighting Efficiency (LE)	25,9 lux/W	Energy Efficiency Index per first cavity	68,7
Lighting Efficiency Class (LEC)	B	Measured air flow rate at best efficiency point (Qbep)	335 m ³ /h
Grease Filtering Efficiency (GFE)	72,0 %	Measured air pressure at best efficiency point (Qbep)	630 Pa
Grease Filtering Efficiency Class (GFEC)	D	Measured electric power input at best efficiency point (Wbep)	226 W
Air flow at minimum speed (Qmin)	208 m ³ /h	Normal Power of the light system (WI)	15 W
Maximum extraction rate	452 m ³ /h		
Intensive extraction rate	594 m ³ /h		
Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)	48 dBA		


Average illumination of the light on the cooking surface (E _{middle})	303 lux
Sound power level at highest setting (L _{wa})	63 dBA

Electrical Connection

Nominal power	305 W	Frequency (Hz)	50-60 Hz
Voltage	220-240 V	Power supply cable length	1500 mm



Not included accessories



KITFCKLTR

1 pcs of Charcoal filter Regenerable* suitable for all the KLT* models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 235(H) x 200 (L) x 10 (D) mm



KITALLFC










Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



RRA90

Round to rectangular adapter 220x90 mm to 150 Ø

Symbols glossary

	24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.		Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.
	Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.		Warning light(s): to advise when filters need changing.
	Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.		Perimeter extraction panels: very efficient and aid noise reduction.
	Intensive/turbo setting: when extra fast extraction is required.		...
	...	