

KLTI12L4MB





Product family	Hood
Hood Type	Island Cooker Hoods
Design	T flat
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Material	Painted material + Glass
EAN code	8017709312251
Hood width	120 cm
Aesthetics	Universal
Colour	Matte Black
Glass Type	Black
Logo	Silk screen



Controls

Control setting	Touch control back-lighted White	Led colour	White
-----------------	-------------------------------------	------------	-------

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	
Auto-Vent 2.0	

Technical Features



No. of lights	2	No. of filters	3
Light type	LED	Anti-grease filters	Aluminium
Light power	7,4 W	Filter replacement indicator	Yes
Dimmer mode	Yes	Vent outlet	150 mm
Light colour temperature range	2700 - 4000 K	Minimum distance from GAS hob	750 mm
Free outlet maximum capacity	820 m³/h	Minimum distance from ELECTRIC hob	650 mm
Motor power	275 W	Non return valve	Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	220	43
Speed 2	335	53
Speed 3	560	65
Intensive speed	739	71

Accessories Included

Tube reduction Yes

Performance / Energy Label



Annual Efficiency Consumption (AEChood) 55 kWh/year

Energy efficiency class (EEC) A

Fluid Dynamic Efficiency (FDE) 33,9

Fluid Dynamic Efficiency class (FDEC) A

Lighting Efficiency (LE) 20,3 lux/W

Lighting Efficiency Class (LEC) D

Grease Filtering Efficiency (GFE) 73,2 %

Grease Filtering Efficiency Class (GFEC) D

Air flow at minumum speed (Qmin) 220 m³/h

Maximum extraction rate 560 m³/h

Intensive extraction rate 739 m³/h

Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) 43 dBA

Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) 66 dBA

Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost) 71 dBA

Energy Efficiency Index per first cavity 51,5

Measured air flow rate at best efficiency point (Qbep) 384 m³/h

Measured air pressure at best efficiency point (Qbep) 376 Pa

Measured electric power input at best efficiency point (Wbep) 151 W

Normal Power of the light system (WI) 15 W

Average illumination of the light on the cooking surface (Emiddle) 300 lux

Sound power level at highest setting (Lwa) 66 dBA

Electrical Connection

Nominal power 291 W
Voltage 220-240 V

Frequency (Hz) 50-60 Hz
Power supply cable length 1500 mm

Compatible Accessories




KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



KITFCKBT











1 pcs of activated carbon filter for hood models KBT* / KBCT*



KITFCKBTR

1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm

Symbols glossary

	24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.		Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.
	Connection between hob and hood		Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.
	A: Product drying performance, measured from A+++ to D / G depending on the product family		...
	Warning light(s): to advise when filters need changing.		Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.
	...		Intensive/turbo setting: when extra fast extraction is required.