

KLTI12L4X

Product family	Hood
Hood Type	Island Cooker Hoods
Design	T flat
Extraction	Ducted out or re-circulation possible
Electronic control	Yes
Material	Stainless Steel + Glass
Type of steel	Brushed
EAN code	8017709312244
Hood width	120 cm
Aesthetics	Universal
Colour	Stainless Steel and Glass
Finishing	Brushed
Glass Type	Black
Logo	Silk screen



Controls

Control setting	Touch control back-lighted White	Led colour	White
-----------------	-------------------------------------	------------	-------

Program / Functions

No. of speeds	3
Intensive speed	
24h air filter function	
Time-setting options	
Auto-Vent 2.0	

Technical Features



No. of lights	2	No. of filters	3
Light type	LED	Anti-grease filters	Aluminium
Light power	7.4 W	Filter replacement indicator	Yes
Dimmer mode	Yes	Vent outlet	150 mm
Light colour	2700 - 4000 K	Minimum distance from GAS hob	750 mm
temperature range		Minimum distance from ELECTRIC hob	650 mm
Free outlet maximum capacity	820 m³/h	Non return valve	Yes
Motor power	275 W		

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	220	43
Speed 2	335	53
Speed 3	560	65
Intensive speed	739	71

Accessories Included

Tube reduction Yes

Performance / Energy Label

	Annual Efficiency Consumption (AEChood)	55 kWh/year	Airbourne acoustical A- weighted sound Power Emission at minimum speed (SPEmin)	43 dBA
	Energy efficiency class (A EEC)		Airborne acoustical A- weighted sound Power Emission at maximum speed (SPEmax)	66 dBA
	Fluid Dynamic Efficiency (FDE)	33.9	Airbourne acoustical A- weighted sound power emission at boost speed (SPEboost)	71 dBA
	Fluid Dynamic Efficiency class (FDEC)	A	Energy Efficiency Index per first cavity	51.5
	Lighting Efficiency (LE)	20.3 lux/W	Measured air flow rate at best efficiency point (Qbep)	384 m³/h
	Lighting Efficiency Class (LEC)	D	Measured air pressure at best efficiency point (Qbep)	376 Pa
	Grease Filtering Efficiency (GFE)	73.2 %	Measured electric power input at best efficiency point (Wbep)	151 W
	Grease Filtering Efficiency Class (GFEC)	D	Normal Power of the light system (WI)	15 W
	Air flow at minimum speed (Qmin)	220 m³/h	Average illumination of the light on the cooking surface (Emiddle)	300 lux
	Maximum extraction rate	560 m³/h	Sound power level at highest setting (Lwa)	66 dBA
	Intensive extraction rate	739 m³/h		

Electrical Connection

Nominal power	291 W	Power supply cable length	1500 mm
Voltage	220-240 V	Plug	No
Frequency (Hz)	50-60 Hz		


Also available

Alternative colours
available

Matte Black

Available colours

KLTI12L4MB




Compatible Accessories




KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



KITFCKBT

1 pcs of activated carbon filter for hood models KBT* / KBCT*



KITFCKBTR

1 pcs of Charcoal filter Regenerable* suitable for all the KBT/KBCT models. * It can be washed in the dishwasher up to 12 times and dry in the oven at max 90° for 60 min. dimension 237,5(H)x245x10 mm

Symbols glossary

 24h:	When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.	 A: Product drying performance, measured from A+++ to D / G depending on the product family
 Filters:	Model has filters to help remove grease from the steam emanating from the pans during cooking.	 Switch off automatically: A special setting, to run after the end of cooking for a pre-set time and then switch off automatically.
 Warning light(s):	to advise when filters need changing.	 Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.
 Intensive/turbo setting:	when extra fast extraction is required.	 Connection between hob and hood
 Dimmering Lights		 Tunable white from warm to cold.