

KPF12BL

Product family	Hood
Hood Type	Decorative wall hood
Design	Chimney
Extraction	Extraction
Material	Stainless Steel + Painted Material
Type of steel	Brushed
EAN code	8017709261634
Hood width	120 cm
Aesthetic	Portofino
Colour	Black
Serigraphy colour	Black
Logo	Applied



Controls

Control setting	Control knobs	Control knobs	Portofino
No. of controls	2	Controls colour	Steel effect

Program / Functions

No. of speeds	3
Intensive speed	

Technical Features



No. of lights	4	No. of filters	4
Light type	LED	Anti-grease filters	Stainless steel
Light Power	4 W	Vent outlet	150 mm
Light color temperature scale (K)	4000 K	Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	815 m³/h	Minimum distance from ELECTRIC hob	650 mm
Motor power	275 W	Non return valve	Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	287	49
Speed 2	389	58

Speed 3	606	67
Intensive speed	777	73

Performance / Energy Label


	Annual Efficiency Consumption (AEChood)	42 kWh/a	Airbourne acoustical A- weighted sound Power	49 dBA
	Energy efficiency class (EEC)	A+	Emission at minimum speed (SPEmin)	
	Fluid Dynamic Efficiency (FDE)	36,3	Airborne acoustical A- weighted sound Power	67 dBA
	Fluid Dynamic Efficiency class (FDEC)	A	Emission at maximum speed (SPEmax)	
	Lighting Efficiency (LE)	74,8 lux/W	Airborne acoustical A- weighted sound power emission at boost speed (SPEboost)	73 dBA
	Lighting Efficiency Class (LEC)	A		
	Grease Filtering Efficiency (GFE)	74,9 %	Time increase factor (F)	0,7
	Grease Filtering Efficiency Class (GFEC)	D	Energy Efficiency Index	41,4
	Air flow at minimum speed (Qmin)	287 m³/h	Measured air flow rate at best efficiency point (Qbep)	400 m³/h
	Air flow at maximum speed (Qmax)	606 m³/h	Measured air pressure at best efficiency point (Pbep)	490 Pa
	Air flow at boost speed (Qboost)	777 m³/h	Measured electric power input at best efficiency point (Wbep)	150 W
			Nominal Power consumption of the light system (WL)	4 W
			Average illumination of the light on the cooking surface (Emiddle)	329 lux
			Sound power level at highest setting (Lwa)	67 dBA

Electrical Connection

Electrical connection rating	280 W	Power supply cable length	1000 mm
Voltage	220-240 V	Plug	Not present
Frequency (Hz)	50-60 Hz		

Also available

Alternative colours available	White, Black, Stainless steel, Red, Turquoise	Available colours	KPF12WH/BL/X/RD/T
--------------------------------------	---	--------------------------	-------------------



Compatible Accessories

FLT6

Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.