

KPF9AN

| | |
|----------------|---------------------------------------|
| Product family | Hood |
| Hood Type | Decorative wall hood |
| Design | Chimney |
| Extraction | Ducted out or re-circulation possible |
| Material | Stainless Steel + Painted Material |
| Type of steel | Brushed |
| EAN code | 8017709236366 |
| Hood width | 90 cm |



Aesthetics

| | | | |
|-------------------|----------------------|------------------------|----------------|
| Aesthetics Colour | Portofino Anthracite | Serigraphy colour Logo | Silver Applied |
|-------------------|----------------------|------------------------|----------------|



Controls

| | | | |
|-----------------|---------------|-----------------|--------------|
| Control setting | Control knobs | Control knobs | Portofino |
| No. of controls | 2 | Controls colour | Steel effect |

Programs / Functions

| | |
|-----------------|---|
| No. of speeds | 3 |
| Intensive speed |  |

Technical Features

| | | | |
|--|---|------------------------------------|-----------------|
|  |  | | |
| No. of lights | 2 | No. of filters | 3 |
| Light type | LED | Anti-grease filters | Stainless steel |
| Light power | 2 W | Vent outlet | 150 mm |
| Light colour | 4000 °K | Minimum distance from GAS hob | 750 mm |
| Free outlet maximum capacity | 815 m ³ /h | Minimum distance from ELECTRIC hob | 650 mm |
| Motor power | 275 W | Non return valve | Yes |

| | Extraction rate IEC 61591 [m ³ /h] | Noise level IEC 60704-2-13 [dB(A)] |
|-----------------|---|------------------------------------|
| Speed 1 | 288 | 48 |
| Speed 2 | 421 | 63 |
| Speed 3 | 630 | 67 |
| Intensive speed | 781 | 72 |

Performance / Energy Label

A*

| | | | |
|--|-----------------------|--|-----------------------|
| Annual Efficiency Consumption (AEChood) | 40 kWh/year | Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) | 48 dB(A) |
| Energy efficiency class (EEC) | A+ | Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) | 67 dB(A) |
| Fluid Dynamic Efficiency (FDE) | 36,2 | Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost) | 72 dB(A) |
| Fluid Dynamic Efficiency class (FDEC) | A | Time increase factor (F) | 1,00 |
| Lighting Efficiency (LE) | 78,2 lux/W | Energy Efficiency Index per first cavity | 40,3 |
| Lighting Efficiency Class (LEC) | A | Measured air flow rate at best efficiency point (Qbep) | 413 m ³ /h |
| Grease Filtering Efficiency (GFE) | 78,5 % | Measured air pressure at best efficiency point (Qbep) | 476 Pa |
| Grease Filtering Efficiency Class (GFEC) | C | Measured electric power input at best efficiency point (Wbep) | 151 W |
| Air flow at minumum speed (Qmin) | 288 m ³ /h | Normal Power of the light system (WI) | 2 W |
| Maximum extraction rate | 630 m ³ /h | Average illumination of the light on the cooking surface (Emiddle) | 172 lux |
| Intensive extraction rate | 781 m ³ /h | Sound power level at highest setting (Lwa) | 67 dB(A) |

Electrical Connection

| | | | |
|---------------|-----------|---------------------------|----------|
| Nominal power | 277 W | Frequency (Hz) | 50-60 Hz |
| Voltage | 220-240 V | Power supply cable length | 1000 mm |


Also available

Alternative colours available

White, Black, Stainless steel, Yellow, Green, Red, Orange

Available colours

KPF9WH-KPF9BL-KPF9X-KP9YW-KPF9OG-KPF9RD-KPF9OR



Not included accessories



FLT6

Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Intensive/turbo setting: when extra fast extraction is required.