


KPFA12T

Product family	Hood
Hood Type	Decorative wall hood
Design	Chimney
Extraction	Extraction
Material	Stainless Steel + Painted Material
Type of steel	Brushed
EAN code	8017709293529
Hood width	120 cm



Aesthetics

Aesthetic Colour	Portofino Turquoise	Serigraphy colour Logo	Black Applied
------------------	---------------------	------------------------	---------------

Controls

Control setting	Control knobs	Control knobs	Portofino
No. of controls	2	Controls colour	Steel effect

Programs / Functions

No. of speeds	3
Intensive speed	

Technical Features

No. of lights	4	No. of filters	4
Light type	LED	Anti-grease filters	Stainless steel
Light Power	4 W	Vent outlet	150 mm
Light color temperature scale (°K)	4000 °K	Minimum distance from GAS hob	650 mm
Light color temperature range	3000° - 5700° °K	Minimum distance from ELECTRIC hob	650 mm
Free outlet maximum capacity	815 m³/h	Non return valve	Yes

Motor power 275 W

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	287	49
Speed 2	389	58
Speed 3	606	67
Intensive speed	777	73

Performance / Energy Label

A+


Annual Efficiency Consumption (AEChood)	42 kWh/a	Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)	73 dB(A)
Energy efficiency class (EEC)	A+	Time increase factor (F)	0,7
Fluid Dynamic Efficiency (FDE)	36,3	Energy Efficiency Index	41,4
Lighting Efficiency (LE)	74,8 lux/W	Measured air flow rate at best efficiency point (Qbep)	400 m³/h
Grease Filtering Efficiency (GFE)	74,9 %	Measured air pressure at best efficiency point (Pbep)	490 Pa
Air flow at minumum speed (Qmin)	287 m³/h	Measured electric power input at best efficiency point (Wbep)	150 W
Air flow at maximum speed (Qmax)	606 m³/h	Nominal Power consumption of the light system (WL)	4 W
Air flow at boost speed (Qboost)	777 m³/h	Average illumination of the light on the cooking surface (Emiddle)	329 lux
Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)	49 dB(A)	Sound power level at highest setting (Lwa)	67 dB(A)
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)	67 dB(A)		

Electrical Connection






Voltage	220-240 V	Power supply cable length	1000 mm
Frequency (Hz)	50-60 Hz		

Also available

Alternative colours available	White, Black, Stainless steel, Red	Available colours	KPF12WH/BL/X/RD
-------------------------------	------------------------------------	-------------------	-----------------



Symbols glossary (TT)

	A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.		Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.
	Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.		Intensive/turbo setting: when extra fast extraction is required.
	...		