

KPFA12X

Product family	Hood
Hood Type	Decorative wall hood
Design	Chimney
Extraction	Extraction
Material	Stainless Steel + Painted Material
Type of steel	Brushed
EAN code	8017709293505
Hood width	120 cm
Aesthetic	Portofino
Colour	Stainless steel
Serigraphy colour	Black
Logo	Applied



Controls

Control setting	Control knobs	Control knobs	Portofino
No. of controls	2	Controls colour	Steel effect

Program / Functions

No. of speeds	3
Intensive speed	

Technical Features



No. of lights	4	No. of filters	4
Light type	LED	Anti-grease filters	Stainless steel
Light Power	4 W	Vent outlet	150 mm
Light color temperature scale (K)	4000 K	Minimum distance from GAS hob	650 mm
Light color temperature range	3000 - 5700 K	Minimum distance from ELECTRIC hob	650 mm
Free outlet maximum capacity	815 m ³ /h	Non return valve	Yes
Motor power	275 W		

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	287	49

Speed 2	389	58
Speed 3	606	67
Intensive speed	777	73

Performance / Energy Label



Annual Efficiency Consumption (AEChood)	42 kWh/a	Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)	73 dBA
Energy efficiency class (EEC)	A+	Time increase factor (F)	0.7
Fluid Dynamic Efficiency (FDE)	36.3	Energy Efficiency Index	41.4
Lighting Efficiency (LE)	74.8 lux/W	Measured air flow rate at best efficiency point (Qbep)	400 m ³ /h
Grease Filtering Efficiency (GFE)	74.9 %	Measured air pressure at best efficiency point (Pbep)	490 Pa
Air flow at minumum speed (Qmin)	287 m ³ /h	Measured electric power input at best efficiency point (Wbep)	150 W
Air flow at maximum speed (Qmax)	606 m ³ /h	Nominal Power consumption of the light system (WL)	4 W
Air flow at boost speed (Qboost)	777 m ³ /h	Average illumination of the light on the cooking surface (Emiddle)	329 lux
Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin)	49 dBA	Sound power level at highest setting (Lwa)	67 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)	67 dBA		

Electrical Connection

Voltage	220-240 V	Power supply cable length	1000 mm
Frequency (Hz)	50-60 Hz	Plug	No

Also available

Alternative colours available	White, Black, Red, Turquese	Available colours	KPF12WH/BL/X/RD/T
--------------------------------------	-----------------------------	--------------------------	-------------------



Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Tunable white from warm to cold.



A+: Energy efficiency class A+ helps to save up to 10% energy compared to class A. Maximum performance with minimum consumption is guaranteed.



Intensive/turbo setting: when extra fast extraction is required.