

KPFA9AN

Product family Hood Type Design Extraction Material Type of steel EAN code Aesthetic Colour Serigraphy colour Logo Hood Decorative wall hood Chimney Extraction Stainless Steel + Painted Material Brushed 8017709251550 Portofino Anthracite Silver Applied



Controls

Control setting No. of controls Control knobs 2



Portofino Steel effect

Program / Functions

No. of speeds Intensive speed



Technical Features

- <u>M</u> -			
No. of lights	2	No. of filters	3
Light type	LED	Anti-grease filters	Stainless steel
Light Power	2 W	Vent outlet	150 mm
Light color temperature scale (°K)	4000 °K	Minimum distance from GAS hob	750 mm
Free outlet maximum capacity	815 m³/h	Minimum distance from ELECTRIC hob	650 mm
Motor power	275 W	Non return valve	Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704- 2-13 [dBA]
Speed 1	288	48
Speed 2	421	63



Speed 3	630	67
Intensive speed	781	72

Electrical Connection

Electrical connection	277 W	Frequency (Hz)	50-60 Hz
rating		Power supply cable	1000 mm
Voltage	220-240 V	length	

Also available

Alternative colours availible	White, Black, Stainless steel, Yellow, Green, Red, Orange	Available colours	KPFA9WH-BL-X-YW-OG- RD-OR
		40 452 435 min 792 - max 1227	
	\sim		



Compatible Accessories

FLT6

Round Charcoal filters (kit 2 pieces)





KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.