

KPRU24X

Product family	Hood
Hood Type	Under cabinet
Design	Canopy pro-style
Venting type	Vented
Electronic control	Yes
Material	Stainless steel
Stainless steel type	Brushed
EAN code	8017709338558
Hood width	24 "
Aesthetics	Classic
Color	Stainless steel
Finishing	Satin
Logo	Embossed



Controls



Control setting

Touch controls

Program / Functions

Speed levels

4

Intensive speed



24h air replacement function



Auto-vent 2.0



Technical Features



No. of lights

2

Lighting

LED

Light power

1.3 W

Dimmable light

Yes

Light color temperature scale (K)

3000 K

Maximum extraction capacity at free mode

599 CFM

Motor power

350 W

No. of filters

2

Anti-grease filters

Stainless steel

Filter replacement indicator

Yes

Vent outlet

5 7/8 "

Minimum distance from gas cooktop

750 "

Minimum distance from electric cooktop

650 "

Non-return valve




Yes

	Extraction rate [CFM]	Noise level [dBA]
Speed level 1	213	54
Speed 2	325.5	63
Speed 3	454	70
Intensive speed	590.5	76

Electrical Connection

Electrical connection rating 353 W
Voltage 120 V
Frequency (Hz) 60 Hz

Power supply cable length 1000 "
Plug No



Compatible Accessories

FLT6U



Symbols glossary



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Dimmering Lights



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Intensive/turbo setting: when extra fast extraction is required.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Warning light(s): to advise when filters need changing.



Touch controls: Easy to use touch controls allow the appliance to be programmed at the touch of a button.



V-Condense System is a system that avoids the drips of condensation that you could show up on the hood within certain circumstance of use.