

KPRU30X

Product family Hood

Hood Type Integrated (semi) hood Design Canopy pro-style

Extraction Extraction

Electronic control Yes Material Stai

MaterialStainless steelType of steelBrushed

EAN code 8017709338565

Hood width 30 "



Aesthetics

AestheticClassicaFinishingSatinColourStainless steelLogoEmbossed

Controls



Control setting Touch control

Technical Features









No. of lights 2 No. of filters 2

Light type LED Anti-grease filters Stainless steel

Light Power 1.3 W Filter replacement Yes indicator

Dimmer mode Yes indicator
Light color temperature 3000 °K Vent outlet 5 7/8 "

scale (°K)

Minimum distance from 750 "

Free outlet maximum 599 CFM GAS hob capacity Minimum distance from 650 "

Motor power 350 W ELECTRIC hob
Non return valve Yes

	Extraction rate IEC 61591 [CFM]	Noise level IEC 60704-2- 13 [dBA]
Speed 1	213	54



Speed 2	325.5	63
Speed 3	454	70
Intensive speed	590.5	76


Electrical Connection


Electrical connection 353 W


rating

Voltage 120 V

Frequency (Hz) 60 Hz Power supply cable 1000 " length









Not included accessories

FLT6

Round Charcoal filters (kit 2 pieces)





Symbols glossary (TT)



24h: When selected this function refreshes the air for c. 10 minutes every hour over a 24 hour period, at minimum speed and an imperceptible noise level.



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Warning light(s): to advise when filters need changing.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Touch controls: Easy to use touch controls allow the appliance to be programmed at the touch of a button.



Intensive/turbo setting: when extra fast extraction is required.



Dimmering Lights



V-Condense System is a system that avoids the drips of condensation that you could show up on the hood within certain circumstance of use.