

# KR37XE

Product family	Hood
Hood Type	Decorative wall hood
Design	Cylindric
Extraction	Extraction
Electronic control	Yes
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709203238
Hood width	37 cm



## Aesthetics

Aesthetic Colour	Universale Stainless steel	Finishing Logo	Satin Embossed
------------------	----------------------------	----------------	----------------





## Controls

Control setting	Electronic buttons	Led color	White
-----------------	--------------------	-----------	-------

## Programme / Functions

No. of speeds	3
Intensive speed	

## Technical Features

			
No. of lights	2	Motor power	270 W
Light type	LED	No. of filters	1
Light Power	1 W	Anti-grease filters	Aluminium
Dimmer mode	Yes	Filter replacement indicator	Yes
Free outlet maximum capacity	690 m³/h	Vent outlet	150 mm

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2- 13 [dB(A)]
Speed 1	280	53
Speed 2	400	60
Speed 3	550	67
Intensive speed	660	70

## Accessories Included

Tube reduction Yes

## Performance / Energy Label


B

**Annual Efficiency Consumption (AEChood)** 58 kWh/a  
**Energy efficiency class (EEC)** B  
**Fluid Dynamic Efficiency (FDE)** 28  
**Fluid Dynamic Efficiency class (FDEC)** A  
**Lighting Efficiency (LE)** 123 lux/W  
**Lighting Efficiency Class (LEC)** A  
**Grease Filtering Efficiency (GFE)** 87 %  
**Grease Filtering Efficiency Class (GFEC)** B  
**Air flow at mininum speed (Qmin)** 280 m³/h  
**Air flow at maximum speed (Qmax)** 550 m³/h  
**Air flow at boost speed (Qboost)** 660 m³/h

**Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)** 53 dB(A)  
**Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)** 67 dB(A)  
**Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)** 70 dB(A)  
**Power Consumption in Off mode (Po)** 0,49 W  
**Time increase factor (F)** 1,00  
**Measured air flow rate at best efficiency point (Qbep)** 332 m³/h  
**Measured air pressure at best efficiency point (Pbep)** 465 Pa  
**Measured electric power input at best efficiency point (Wbep)** 153 W  
**Nominal Power consumption of the light system (WL)** 2 W  
**Average illumination of the light on the cooking surface (Emiddle)** 270 lux  
**Sound power level at highest setting (Lwa)** 67 dB(A)

## Electrical Connection

## Charcoal filter KITFC161



---

## Not included accessories

---



**RCKF2**

Remote control



**KITALLFC**

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary (TT)

---



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Warning light(s): to advise when filters need changing.



Intensive/turbo setting: when extra fast extraction is required.



B: Product energy rating, measured from A+++ to D / G depending on the product family.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.



Dimmering Lights