

# KS59POE2

Product family	Hood
Hood Type	Decorative wall hood
Design	Chimney
Extraction	Extraction
Material	Heat-moulded
Type of steel	Brushed
EAN code	8017709303242
Hood width	60 cm
Aesthetic	Coloniale
Colour	Cream
Components finishing	Antique brass
Logo	Applied





## Controls

Control setting	Control knobs	Control knobs	Colonial
No. of controls	2	Controls colour	Old Brass

## Program / Functions

No. of speeds	3
Intensive speed	

## Technical Features

			
No. of lights	2	No. of filters	2
Light type	LED	Anti-grease filters	Stainless steel
Light Power	1 W	Vent outlet	150 mm
Light color temperature scale (K)	3000 K	Minimum distance from GAS hob	750 mm
Free outlet maximum capacity	820 m <sup>3</sup> /h	Minimum distance from ELECTRIC hob	650 mm
Motor power	275 W	Non return valve	Yes

	Extraction rate IEC 61591 [m <sup>3</sup> /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	311	49
Speed 2	439	57

Speed 3	522	62
Intensive speed	754	70

## Performance / Energy Label




<b>Annual Efficiency Consumption (AEChood)</b>	58 kWh/a	<b>Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)</b>	49 dBA
<b>Energy efficiency class (EEC)</b>	A	<b>Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)</b>	63 dBA
<b>Fluid Dynamic Efficiency (FDE)</b>	29.9	<b>Airbourne acoustical A-weighted sound power emission at boost speed (SPEboost)</b>	70 dBA
<b>Fluid Dynamic Efficiency class (FDEC)</b>	A	<b>Time increase factor (F)</b>	0.9
<b>Lighting Efficiency (LE)</b>	118.2 lux/W	<b>Energy Efficiency Index</b>	52.3
<b>Lighting Efficiency Class (LEC)</b>	A	<b>Measured air flow rate at best efficiency point (Qbep)</b>	418 m <sup>3</sup> /h
<b>Grease Filtering Efficiency (GFE)</b>	70.8 %	<b>Measured air pressure at best efficiency point (Pbep)</b>	443 Pa
<b>Grease Filtering Efficiency Class (GFEC)</b>	D	<b>Measured electric power input at best efficiency point (Wbep)</b>	172 W
<b>Air flow at minumum speed (Qmin)</b>	311 m <sup>3</sup> /h	<b>Nominal Power consumption of the light system (WL)</b>	2 W
<b>Air flow at maximum speed (Qmax)</b>	522 m <sup>3</sup> /h	<b>Average illumination of the light on the cooking surface (Emiddle)</b>	260 lux
<b>Air flow at boost speed (Qboost)</b>	754 m <sup>3</sup> /h	<b>Sound power level at highest setting (Lwa)</b>	63 dBA

## Electrical Connection

<b>Electrical connection rating</b>	277 W	<b>Power supply cable length</b>	1000 mm
<b>Voltage</b>	220-240 V	<b>Plug</b>	Not present
<b>Frequency (Hz)</b>	50-60 Hz		

## Also available

<b>Alternative colours available</b>	Anthracite	<b>Available colours</b>	KS59AOE2
--------------------------------------	------------	--------------------------	----------



---

## Compatible Accessories

---

### FLT6

Round Charcoal filters (kit 2 pieces)







### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary

---

- |  |   |   |   |
|--|---|---|---|
|  | Energy efficiency class A   |  | Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking. |
|  | Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen. |  | Intensive/turbo setting: when extra fast extraction is required.  |