

KSEC91XE3

Product family	Hood
Hood Type	Integrated (semi) hood
Design	Visible front panel
Extraction	Extraction
Material	Stainless Steel + Painted Material
EAN code	8017709343354
Hood width	90 cm
Aesthetic	Universale
Colour	Stainless steel/Black
Serigraphy colour	Black
Logo	Silk screen





Controls

Control setting	Slider
-----------------	--------

Program / Functions

No. of speeds	3
---------------	---

Technical Features

			
No. of lights	2	No. of filters	1
Light type	LED	Anti-grease filters	Metallic multilayer
Light Power	4 W	Vent outlet	120 mm
Light color temperature scale (K)	4000 K	Minimum distance from GAS hob	650 mm
Free outlet maximum capacity	315 m ³ /h	Minimum distance from ELECTRIC hob	450 mm
Motor power	115 W		

	Extraction rate IEC 61591 [m ³ /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	170	58
Speed 2	240	66

Speed 3	305	72
------------	-----	----

Accessories included



Charcoal filters included Yes

Performance / Energy Label



Annual Efficiency Consumption (AEC _{hood})	60 kWh/a	Airborne acoustical A-weighted sound Power Emission at minimum speed (SPE _{min})	58 dBA
Energy efficiency class (EEC)	C	Airborne acoustical A-weighted sound Power Emission at maximum speed (SPE _{max})	72 dBA
Fluid Dynamic Efficiency (FDE)	10	Time increase factor (F)	1.6
Fluid Dynamic Efficiency class (FDEC)	E	Energy Efficiency Index	84.8
Lighting Efficiency (LE)	11 lux/W	Measured air flow rate at best efficiency point (Q _{bep})	167 m ³ /h
Lighting Efficiency Class (LEC)	E	Measured air pressure at best efficiency point (P _{bep})	198 Pa
Grease Filtering Efficiency (GFE)	40 %	Measured electric power input at best efficiency point (W _{bep})	92 W
Grease Filtering Efficiency Class (GFEC)	G	Nominal Power consumption of the light system (WL)	8 W
Air flow at minimum speed (Q _{min})	170 m ³ /h	Average illumination of the light on the cooking surface (E _{middle})	90 lux
Air flow at maximum speed (Q _{max})	305 m ³ /h	Sound power level at highest setting (L _{wa})	72 dBA

Electrical Connection

Electrical connection rating	133 W	Power supply cable length	1500 mm
Voltage	220-240 V	Plug	Not present
Frequency (Hz)	50 Hz		



Compatible Accessories



KITFC111

Charcoal filters round Kit 1 piece

Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Charcoal filters: Extracting through charcoal filters or directly to the exterior lessens strong cooking odours considerably.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.

