KSED65BE

Product family	Hood
Hood Type	Chimney Cooker Hoods
Design	Chimney
Extraction	Ducted out or re-circulation possible
Material	Painted material
Type of steel	Brushed
EAN code	8017709212070
Hood width	60 cm
Aesthetics	Victoria
Colour	White
Logo	Silk screen



Controls

Control setting	Slider

Program / Functions

No. of speeds	3

Technical Features

No. of lights	2	**No. of filters**	2
Light type	LED	**Anti-grease filters**	Aluminium
Light power	2 W	**Vent outlet**	150 mm
Light colour temperature scale (K)	4000 K	**Minimum distance from GAS hob**	750 mm
Free outlet maximum capacity	600 m³/h	**Minimum distance from ELECTRIC hob**	650 mm
Motor power	200 W	**Non return valve**	Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	351	53
Speed 2	420	57

Speed 3	635	67

Performance / Energy Label



Annual Efficiency Consumption (AEChood)	60 kWh/year
Energy efficiency class (EEC)	B
Fluid Dynamic Efficiency (FDE)	26
Fluid Dynamic Efficiency class (FDEC)	B
Lighting Efficiency (LE)	100,2 lux/W
Lighting Efficiency Class (LEC)	A
Grease Filtering Efficiency (GFE)	74,4 %
Grease Filtering Efficiency Class (GFEC)	D
Air flow at minumum speed (Qmin)	351 m³/h
Maximum extraction rate	635 m³/h

Airbourne acouistical A-weighted sound Power Emission at minimum speed (SPEmin)	53 dBA
Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)	67 dBA
Time increase factor (F)	1,1
Energy Efficiency Index per first cavity	62,2
Measured air flow rate at best efficiency point (Qbep)	355 m³/h
Measured air pressure at best efficiency point (Qbep)	385 Pa
Measured electric power input at best efficiency point (Wbep)	146 W
Normal Power of the light system (WI)	2 W
Average illumination of the light on the cooking surface (Emiddle)	221 lux
Sound power level at highest setting (Lwa)	67 dBA


Electrical Connection

Nominal power	202 W
Voltage	220-240 V
Frequency (Hz)	50-60 Hz

Power supply cable length	1000 mm
Plug	No

Also available

Alternative colours availible	Black, Stainless steel, Cream


171
207
400
min.810-max.1170
252
600
514

Compatible Accessories



FLT6

Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.

