

# KSED65BE

Product family	Hood
Hood Type	Decorative wall hood
Design	Chimney
Extraction	Extraction
Material	Painted material
Type of steel	Brushed
EAN code	8017709212070
Hood width	60 cm
Aesthetic	Victoria
Colour	White
Logo	Silk screen



## Controls

Control setting	Slider
-----------------	--------

## Program / Functions

No. of speeds	3
---------------	---

## Technical Features



No. of lights	2	No. of filters	2
Light type	LED	Anti-grease filters	Aluminium
Light Power	2 W	Vent outlet	150 mm
Light color temperature scale (K)	4000 K	Minimum distance from GAS hob	750 mm
Free outlet maximum capacity	600 m³/h	Minimum distance from ELECTRIC hob	650 mm
Motor power	200 W	Non return valve	Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	351	53
Speed 2	420	57

Speed 3	635	67
---------	-----	----

## Performance / Energy Label


	
<b>Annual Efficiency Consumption (AEChood)</b>	60 kWh/a
<b>Energy efficiency class (EEC)</b>	B
<b>Fluid Dynamic Efficiency (FDE)</b>	26
<b>Fluid Dynamic Efficiency class (FDEC)</b>	B
<b>Lighting Efficiency (LE)</b>	100,2 lux/W
<b>Lighting Efficiency Class (LEC)</b>	A
<b>Grease Filtering Efficiency (GFE)</b>	74,4 %
<b>Grease Filtering Efficiency Class (GFEC)</b>	D
<b>Air flow at minimum speed (Qmin)</b>	351 m³/h
<b>Air flow at maximum speed (Qmax)</b>	635 m³/h
<b>Airbourne acoustical weighted sound Power Emission at minimum speed (SPEmin)</b>	Airbourne acoustical A- 53 dBA
<b>Airbourne acoustical weighted sound Power Emission at maximum speed (SPEmax)</b>	Airborne acoustical A- 67 dBA
<b>Time increase factor (F)</b>	1,1
<b>Energy Efficiency Index</b>	62,2
<b>Measured air flow rate at best efficiency point (Qbep)</b>	355 m³/h
<b>Measured air pressure at best efficiency point (Pbep)</b>	385 Pa
<b>Measured electric power input at best efficiency point (Wbep)</b>	146 W
<b>Nominal Power consumption of the light system (WL)</b>	2 W
<b>Average illumination of the light on the cooking surface (Emiddle)</b>	221 lux
<b>Sound power level at highest setting (Lwa)</b>	67 dBA

## Electrical Connection

<b>Electrical connection rating</b>	202 W	<b>Power supply cable length</b>	1000 mm
<b>Voltage</b>	220-240 V	<b>Plug</b>	Not present
<b>Frequency (Hz)</b>	50-60 Hz		

## Also available

<b>Alternative colours available</b>	Black, Stainless steel, Cream
--------------------------------------	-------------------------------



## Compatible Accessories

### FLT6

Round Charcoal filters (kit 2 pieces)



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304. The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary

---



**Filters:** Model has filters to help remove grease from the steam emanating from the pans during cooking.



**Lights:** All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.

