

# KSED65BE

Product family Hood

Hood Type Decorative wall hood

Design Chimney
Extraction Extraction
Material Painted material
Type of steel Brushed

EAN code 8017709212070

Hood width 60 cm



#### **Aesthetics**

Aesthetic Victoria Logo Silk screen

Colour White

### **Controls**

Control setting Slider

## **Programme / Functions**

No. of speeds 3

#### **Technical Features**



No. of lights2No. of filters2Light typeLEDAnti-grease filtersA

Light typeLEDAnti-grease filtersAluminiumLight Power2 WVent outlet150 mmLight color temperature4000 °KMinimum distance from750 mm

scale (°K) GAS hob

Free outlet maximum 600 m³/h Minimum distance from 650 mm capacity ELECTRIC hob

Motor power 200 W Non return valve Yes



	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dB(A)]
Speed 1	351	53
Speed 2	420	57
Speed 3	635	67

### Performance / Energy Label

/	A.

**Annual Efficiency** 60 kWh/a Consumption (AEChood) Energy efficieency class B (EEC) Fluid Dynamic Efficiency 26 (FDE) Fluid Dynamic Efficiency B class (FDEC) Lighting Efficiency (LE) 100,2 lux/W Lighting Efficiency Class A (LEC) **Grease Filtering** 74,4 % Efficiency (GFE)

**Grease Filtering** Efficiency Class (GFEC) Air flow at minumum 351 m<sup>3</sup>/h speed (Qmin) Air flow at maximum 635 m<sup>3</sup>/h speed (Qmax)

Airbourne acouistical A- 53 dB(A) weighted sound Power **Emission at minimum** speed (SPEmin) Airborne acoustical A-67 dB(A) weighted sound Power **Emission at maximum** speed (SPEmax) Time increase factor (F) 1,1 **Energy Efficiency Index** 62.2 Measured air flow rate 355 m<sup>3</sup>/h at best efficiency point (Qbep) Measured air pressure 385 Pa at best efficiency point (Pbep) Measured electric 146 W power input at best efficiency point (Wbep) **Nominal Power** 2 W consumption of the light system (WL) Average illumination of 221 lux

the light on the cooking surface (Emiddle)

67 dB(A)

Sound power level at highest setting (Lwa)

#### **Electrical Connection**

Plug **Electrical connection** rating

Voltage

Not present 202 W

220-240 V

Frequency (Hz) Power supply cable length


50-60 Hz 1000 mm

#### Also available

Alternative colours availible

Black, Stainless steel, Cream







## Not included accessories

FLT6



Round Charcoal filters (kit 2 pieces)



#### **KITALLFC**

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



## Symbols glossary (TT)



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.

