

KSED65PE

Product family Hood

Hood Type Decorative wall hood

Design Chimney
Extraction Extraction
Material Painted material

Type of steel Brushed

EAN code 8017709206062

Hood width 60 cm



Aesthetics

Aesthetic Victoria Logo Silk screen

Colour Cream

Controls

Control setting Slider

Programs / Functions

No. of speeds 3

Technical Features



Motor power

No. of lights2No. of filters2Light typeLEDAnti-grease filtersAl

Light typeLEDAnti-grease filtersAluminiumLight Power1 WVent outlet150 mmLight color temperature4000 °KMinimum distance from750 mm

scale (°K) GAS hob

200 W

Free outlet maximum 600 m³/h Minimum distance from 650 mm capacity ELECTRIC hob

Non return valve Yes



| | Extraction rate IEC 61591 [m³/h] | Noise level IEC 60704-2-13 [dB(A)] |
|------------|-------------------------------------|---------------------------------------|
| Speed 1 | 351 | 53 |
| Speed 2 | 420 | 57 |
| Speed 3 | 635 | 67 |

Performance / Energy Label

В

60 kWh/a **Annual Efficiency** Airbourne acouistical A- 53 dB(A) Consumption (AEChood) Energy efficieency class B (EEC)

74,4 %

351 m³/h

635 m³/h

Fluid Dynamic Efficiency 26 (FDE)

Fluid Dynamic Efficiency B

class (FDEC) Lighting Efficiency (LE) 100,2 lux/W

Lighting Efficiency Class A

(LEC)

Efficiency (GFE) **Grease Filtering**

Efficiency Class (GFEC)

Air flow at minumum speed (Qmin)

Air flow at maximum

speed (Qmax)

Grease Filtering

weighted sound Power Emission at minimum speed (SPEmin)

Airborne acoustical Aweighted sound Power Emission at maximum speed (SPEmax)

Time increase factor (F) 1,1 **Energy Efficiency Index** 62 2 Measured air flow rate 355 m³/h at best efficiency point

(Qbep)

Measured air pressure at best efficiency point

(Pbep)

Measured electric 146 W power input at best efficiency point (Wbep)

Nominal Power consumption of the light

system (WL)

221 lux

2 W

67 dB(A)

385 Pa

Average illumination of the light on the cooking surface (Emiddle)

Sound power level at highest setting (Lwa) 67 dB(A)

Electrical Connection

Electrical connection

rating

Voltage

202 W

220-240 V

Frequency (Hz) Power supply cable 50-60 Hz 1000 mm


length

Also available

Alternative colours availible

White, Black, Stainless







Not included accessories

FLT6



Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes



Symbols glossary (TT)



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



B: Product energy rating, measured from A+++ to D / G depending on the product family.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.