

# KSED65PE

Product family	Hood
Hood Type	Decorative wall hood
Design	Chimney
Extraction	Extraction
Material	Painted material
Type of steel	Brushed
EAN code	8017709206062
Hood width	60 cm
Aesthetic	Victoria
Colour	Cream
Logo	Silk screen



## Controls

Control setting	Slider
-----------------	--------

## Program / Functions

No. of speeds	3
---------------	---

## Technical Features

		<b>No. of lights</b>	2	<b>No. of filters</b>	2
		<b>Light type</b>	LED	<b>Anti-grease filters</b>	Aluminium
		<b>Light Power</b>	1 W	<b>Vent outlet</b>	150 mm
		<b>Light color temperature scale (K)</b>	4000 K	<b>Minimum distance from GAS hob</b>	750 mm
		<b>Free outlet maximum capacity</b>	600 m <sup>3</sup> /h	<b>Minimum distance from ELECTRIC hob</b>	650 mm
		<b>Motor power</b>	200 W	<b>Non return valve</b>	Yes

	Extraction rate IEC 61591 [m <sup>3</sup> /h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	351	53
Speed 2	420	57

Speed 3	635	67
------------	-----	----

## Performance / Energy Label



Annual Efficiency Consumption (AEChood)	60 kWh/a	Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin)	53 dBA
Energy efficiency class (EEC)	B	Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax)	67 dBA
Fluid Dynamic Efficiency (FDE)	26	Time increase factor (F)	1,1
Fluid Dynamic Efficiency class (FDEC)	B	Energy Efficiency Index	62,2
Lighting Efficiency (LE)	100,2 lux/W	Measured air flow rate at best efficiency point (Qbep)	355 m <sup>3</sup> /h
Lighting Efficiency Class (LEC)	A	Measured air pressure at best efficiency point (Pbep)	385 Pa
Grease Filtering Efficiency (GFE)	74,4 %	Measured electric power input at best efficiency point (Wbep)	146 W
Grease Filtering Efficiency Class (GFEC)	D	Nominal Power consumption of the light system (WL)	2 W
Air flow at minumum speed (Qmin)	351 m <sup>3</sup> /h	Average illumination of the light on the cooking surface (Emiddle)	221 lux
Air flow at maximum speed (Qmax)	635 m <sup>3</sup> /h	Sound power level at highest setting (Lwa)	67 dBA

## Electrical Connection

Electrical connection rating	202 W	Power supply cable length	1000 mm
Voltage	220-240 V	Plug	Not present
Frequency (Hz)	50-60 Hz		

## Also available

Alternative colours available	White, Black, Stainless steel
-------------------------------	-------------------------------



---

## Compatible Accessories

---

### FLT6

Round Charcoal filters (kit 2 pieces)



### KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

---

## Symbols glossary

---



**Filters:** Model has filters to help remove grease from the steam emanating from the pans during cooking.



**Lights:** All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.