

KSED75XE

Product family	Hood
Hood Type	Chimney Cooker Hoods
Design	Chimney
Extraction	Ducted out or re-circulation possible
Material	Stainless steel
Type of steel	Brushed
EAN code	8017709206086
Aesthetics	Universal
Colour	Stainless steel
Finishing	Brushed
Logo	Embossed



Controls

Control setting	Slider
-----------------	--------

Program / Functions

No. of speeds	3
---------------	---

Technical Features

			
No. of lights	2	No. of filters	2
Light type	LED	Anti-grease filters	Aluminium
Light power	1 W	Vent outlet	150 mm
Light colour	4000 °K	Minimum distance from GAS hob	750 mm
Free outlet maximum capacity	595 m³/h	Minimum distance from ELECTRIC hob	650 mm
Motor power	200 W	Non return valve	Yes

	Extraction rate IEC 61591 [m³/h]	Noise level IEC 60704-2-13 [dBA]
Speed 1	351	53
Speed 2	420	57

Speed 3	635	67
------------	-----	----

Performance / Energy Label



Annual Efficiency Consumption (AEChood) 60 KWh/year

Energy efficiency class (EEC) B

Fluid Dynamic Efficiency (FDE) 26

Fluid Dynamic Efficiency class (FDEC) B

Lighting Efficiency (LE) 100,2 lux/W

Lighting Efficiency Class (LEC) A

Grease Filtering Efficiency (GFE) 74,4 %

Grease Filtering Efficiency Class (GFEC) D

Air flow at minumum speed (Qmin) 351 m³/h

Maximum extraction rate 635 m³/h

Airbourne acoustical A-weighted sound Power Emission at minimum speed (SPEmin) 53 dBA

Airborne acoustical A-weighted sound Power Emission at maximum speed (SPEmax) 67 dBA

Time increase factor (F) 1,1

Energy Efficiency Index per first cavity 62,2

Measured air flow rate at best efficiency point (Qbep) 355 m³/h

Measured air pressure at best efficiency point (Qbep) 385 Pa

Measured electric power input at best efficiency point (Wbep) 146 W

Normal Power of the light system (WI) 2 W


Average illumination of the light on the cooking surface (Emiddle) 221 lux

Sound power level at highest setting (Lwa) 67 dBA

Electrical Connection

Nominal power 202 W
Voltage 220-240 V

Frequency (Hz) 50-60 Hz
Power supply cable length 1000 mm



Compatible Accessories



FLT6

Round Charcoal filters (kit 2 pieces)



KITALLFC

Universal Charcoal filter Stainless Steel AISI 304 The filter can be washed in dishwasher 50 °C (water and suitable detergent) and to dry it put in the oven 180°C 25 minutes

Symbols glossary



Filters: Model has filters to help remove grease from the steam emanating from the pans during cooking.



Lights: All cooker hoods feature lights to illuminate the cooking area or add to the ambience of the kitchen.